

WRS COMPLETION REPORT

COMPLETIONS SEC 33 TWP 16S RGE 37E
P1/ 30-T-0012 01/25/88 30-025-30124-0000 PAGE 1

NMEX LEA * 330FSL 1980FWL SEC SE SW
STATE COUNTY FOOTAGE SPOT
AMERIND OIL D DO
OPERATOR WELL CLASS INIT FIN

3 MEYERS
WELL NO. LEASE NAME
3795KB 3780GR SHIPP
OPER ELEV FIELD POOL/AREA

API 30-025-30124-0000
LEASE TYPE NO. PERMIT OR WELL I.D. NO.

11/15/1987 12/26/1987 ROTARY OIL
SPUD DATE COMP DATE TYPE TOOL STATUS
11350 STRAWN LANDIS DRLG 3 RIG SUB 14
PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 11294 PB 11254 FM/TD STRAWN
DRILLERS T.D. LOG T.D. PLUG BACK TD OLD T.D. FORM T.D.

LOCATION DESCRIPTION

7 MI SE LOVINGTON, NM

CASING/LINER DATA

CSG 12 3/4 @ 407 W/ 350 SACKS
CSG 8 5/8 @ 4203 W/ 1500 SACKS
CSG 5 1/2 @ 11294 W/ 350 SACKS

TUBING DATA

TBG 2 7/8 AT 11000

INITIAL POTENTIAL

IPF 140BOPD 120 MCFD 20/64CK 24HRS
STRAWN PERF W/ 46/IT 11098-11170 GROSS
PERF 11098-11102 11130-11170
ACID 11098-11170 7200GALS

ADDTVNTGN

500 SCF PER BBL
TP 180
GTY 43.0 GOR 857
CP PKR

TYPE	FORMATION	LTH	TOP DEPTH/SUB	BSE DEPTH/SUB
LOG	RUSTLER		2018 1777	
LOG	YATES		3084 711	
LOG	SN ANDRS		4943 -1148	

CONTINUED IC# 300257036187

Copyrighted 1988
Petroleum
Information Corporation

Petroleum Information

DB a company of
The Dun & Bradstreet Corporation

PI-WRS-GET
Form No 187

COMPLETIONS SEC 33 TWP 16S RGE 37E
PI# 30-T-0012 01/25/88 30-025-30124-0000 PAGE 2

AMERIND OIL D DO
3 MEYERS

TYPE	FORMATION	LTH	TOP	DEPTH/SUB	BSE	DEPTH/SUB
LOG	GLORIETA		6162	-2367		
LOG	PADDOCK		6361	-2566		
LOG	TUBB		7843	-4048		
LOG	DRINKARD		8034	-4239		
LOG	WOLFCAMP		9581	-5786		
LOG	PNNSYLVN		10345	-6550		
LOG	STRAWN		11069	-7274		

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS 6000-11294 DILL 4200-11294 NEUT 4200-11294 DENL
LOGS 1000-11294 SONL

DRILLING MEDIA /TYPE,DEPTH/

10890 8.6 PPG

DRILLING PROGRESS DETAILS

AMERIND OIL
500 WILCO BLDG
MIDLAND, TX 79701
915-682-8717
10/30 LOC/1987/
11/20 DRLG 4052
11/25 DRLG 6713
12/04 DRLG 10890, VIS 32
12/11 11294 TD, PB 11254, WOCT
TD REACHED 12/07/87 RIG REL 12/09/87
01/18 11294 TD, PB 11254
COMP 12/26/87, IPF 140 BO, 120 MCFGPD THRU
20/64 CHK, GOR 857, GTY 43,
CP PKR, FTP 180
PROD ZONE - STRAWN 11098-11170
NO CORES OR DSTS RPTD