

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Cisco/Shale	10999
T. Salt	T. Strawn	11342
B. Salt	T. Atoka	11912
T. Yates	T. Miss	12216
T. 7 Rivers	T. Devonian	
T. Queen	T. Silurian	
T. Grayburg	T. Montoya	
T. San Andres	T. Simpson	5040
T. Glorieta	T. McKee	6378
T. Paddock	T. Ellenburger	
T. Blinberry	T. Gr. Wash	
T. Tubb	T. Granite	7866
T. Drinkard	T. Delaware Sand	
T. Abo	T. Bone Springs	8562
T. Wolfcamp LS	T. L. Strawn LS	10044
T. Penn.	T. Strawn Clastic	11742
T. Cisco (Hough C)	T.	

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefee	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Qtzite
Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....
No. 4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	440	440	Surface, Rock				
440	1780	1340	Redbeds				
1780	2460	680	Redbeds, Anhy				
2460	3510	1050	Anhy, Salt				
3510	4015	505	Anhy				
4015	4380	365	Anhy, Lm				
4380	7920	3540	Dolo				
7920	8310	390	Dolo, Sd				
8310	8700	390	Dolo				
8700	9000	300	Dolo, Sh				
9000	10100	1100	Dolo				
10100	10600	500	Dolo, Cht, Lm, Sh				
10600	11340	740	Dolo, Lm, Sh				
11340	11760	420	Lm, Sh				
11760	12420	660	Lm, Sh, Sd				