

OIL CONSERVATION DIVISION
P. O. BOX 2068
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-6721

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - C" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator W. A. Moncrief, Jr.	8. Farm or Lease Name State "8"
3. Address of Operator 400 Metro Bldg., Midland, Texas 79701	9. Well No. 2
4. Location of Well UNIT LETTER B 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 8 TOWNSHIP 16S RANGE 34E	10. Field and Pool, or Wildcat N. Hume Wolfcamp
15. Elevation (Show whether DF, RT, GR, etc.) 4134.4 gd., 4150.4 KB	12. County JEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☐	PLUG AND ABANDONMENT ☐
FULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Well was spudded at 7:30 AM 6/10/88
- Drilled 17½" hole to 430' & ran 13 3/8" J-55 68# ST & C casing to 430' & cemented w/450 sax class "C" w/2% CaCl on 6/10/88. Cement circulated 106 sax. WOC 18 hrs. Tested csg to 1000# for 30 minutes. Held ok.
- Drilled 11" hole to 4450'. Ran 8 5/8" 32# K-55 ST & C casing to 4450' on 6/17/88. Cemented w/1100 sax Howcolite + 200 sax class "C" w/2% CaCl. Cement circulated 40 sax. WOC 18 hrs. Tested casing to 1000# for 30 minutes. Held ok.
- Drilled 7 7/8" hole to 10,140' driller, 10,140 Welex & 10,144 strap. Ran 5½" 17# N-80 LT & C casing on 7/2/88. Cemented w/450 sax class "H" w/.5# per sack of HALAD 9 and 10# per sack of micro-bond. P.D. 2:30 AM 7/2/88. Tested casing to 2500# for 30 minutes. Held ok.
- Will run CBL to determine top cement outside casing.
- Mud properties at T.D. were mw 8.8#, vis 39, W.L. 14, FC 1/32, Ph 10 & Chlorides 2000 PPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CHIEF Deputy E. Tharston TITLE Exploration Manager DATE 7/5/88
ORIGINAL SIGNED BY JERRY CRYSTON
DISTRICT SUPERVISOR
DATE _____ TITLE _____ DATE _____
SIGNATURES OF APPROVAL, IF ANY: