

NO. OF COPIES RECEIVED	
DISTRIBUTION	
DATE	
BY	
U.S.G.S.	
FIELD OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
 Supersedes O-11  
 C-102 and C-103  
 Effective 1-1-65

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR OPERATIONS TO BE CARRIED OUT IN A DIFFERENT RESERVOIR. USE APPLICATIONS FOR PERMITS OR PRODUCTION OPERATIONS.)

5. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Firm or Lease Name <b>Chace-McKamey</b>
9. Well No. <b>1</b>
10. Field and Pool, or Subunit <b>Townsend Permo Upper Per</b>
11. Elevation (Show whether DF, RT, GR, etc.) <b>4051' GR</b>
12. County <b>Lea</b>

1. Name of Operator  
**ELK OIL COMPANY**

2. Address of Operator  
**Post Office Box 310, Roswell, New Mexico 88202-0310**

3. Location of Well  
UNIT LETTER **I** **2310** FEET FROM THE **South** LINE AND **990** FEET FROM THE **East** LINE, SECTION **13** TOWNSHIP **16S** RANGE **34E** N.M.P.M.


Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
REPAIR OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Reached TD of 10,900' on 08/27/88. Plugged back as follows:  
 100' Plug (30 sxs) @ 10,783 to 10,683.  
 100' Plug (30 sxs) @ 9,872 to 9,772.  
 100' Plug (30 sxs) @ 7,913 to 7,813.  
 100' Plug (30 sxs) @ 6,187 to 6,087.  
 100' Plug (30 sxs) @ 4,993 to 4,893.  
 All plugs displaced with drilling mud. Ran 4801' of 4½", 11.6#, N-80 and K-55 Casing. Cemented with 350 sxs Class C 50/50 Poz, containing 2% Gel, 5# Salt and ¼# Flocele. WOC 18 hours; tested 30 minutes, held okay. Prep to perforate and test.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

OPERATOR:  TITLE President DATE 08/31/88

APPROVED BY: **ORIGINAL SIGNED BY JERRY SEXTON** TITLE DISTRICT I SUPERVISOR DATE SEP 6 1988

CONDITIONS OF APPROVAL, IF ANY: