

Attachment to Form C-105

Greenhill Petroleum Corporation
Lovington Grayburn San Andres Field
Lovington San Andres Unit Well No. 60
April 1990

Item #26 - Perforation Record

<u>Interval</u>	<u>Size</u>	<u>Number</u>
4642 - 4646	.41	16
4649 - 4662	.41	12
4697 - 4707	.41	40
4850 - 4857	.41	28
4871 - 4883	.41	48
4886 - 4910	.41	96
4914 - 4919	.41	20
4921 - 4925	.41	16
4927 - 4936	.41	36
5102 - 5113	.41	44
5172 - 5175	.41	12
5177 - 5179	.41	8
5181 - 5190	.41	36
5192 - 5194	.41	8
5196 - 5200	.41	16
5203 - 5216	.41	52

Item #27 - Acid, Shot, Fracture, Cement, Squeeze, Etc.

<u>Depth Interval</u>	<u>Amount and Kind Material Used</u>
5172-75, 5177-79, 5181-90, 5192-94, 5196-5200, 5203-16	7950 gallons gelled 20% HCl NEFE acid and 250 gallons 28% HCl NEFE acid.
5102-13	1650 gallons gelled 20% HCl NEFE acid and 110 gallons 28% HCl NEFE acid
4850-57, 4871-83, 4886-4910, 4914-19, 4921-25, 4927-36	7700 gallons gelled 20% HCl NEFE acid and 610 gallons 28% HCl NEFE acid
4697-4707	500 gallons gelled 20% HCl NEFE acid and 200 gallons 28% HCl NEFE acid
4642-46, 4649-62	450 gallons gelled 20% HCl NEFE acid