— Submit 3 Copies to Appropriate District Office		of New Mexico Natural Resources Department	Form C-103 Revised 1-1-89
DISTRICT I	OIL CONSER	VATION DIVISION	WELL API NO.
P.O. Box 1980, Hobbs, NM 88240). Box 2088	30-025-30785
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New	v Mexico 87504-2088	5. Indicate Type of Lease STATE X FEE
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 8741	0		6. State Oil & Gas Lease No. LG-9178-1
(DO NOT USE THIS FORM FOR F DIFFERENT RES (FORM	OTICES AND REPORTS PROPOSALS TO DRILL OR T SERVOIR. USE "APPLICATIC A C-101) FOR SUCH PROPOS	O DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL GAS WELL X WELL [OTHER		Adobe - State
2. Name of Operator			8. Well No.
Cox Oil & Gas, Inc.	<u></u>		11
3. Address of Operator	+- 2000 D-11		9. Pool name or Wildcat
2200 Ross Avenue, Sui 4. Well Location	te 3600, Dallas, 1	'exas 75201	Wildcat 2
			74 Feet From The East Line
Section 5	Township 15 Sout	h Range 35 East how whether DF, RKB, RT, GR. etc.)	NMPM Lea County
		4027.4 Gr.	
		Indicate Nature of Notice, R	epoid of other sum
	NTENTION TO: Plug and abando Change plans		BSEQUENT REPORT OF: ALTERING CASING GOPNS. PLUG AND ABANDONMENT
NOTICE OF II	NTENTION TO: PLUG AND ABANDA CHANGE PLANS	ON X REMEDIAL WORK COMMENCE DRILLING CASING TEST AND C	ALTERING CASING
NOTICE OF II	NTENTION TO: PLUG AND ABANDA CHANGE PLANS	ON X REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CL OTHER:	ALTERING CASING
NOTICE OF II PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed Of work) SEE RULE 1103. Well drilled as a di plugs: #1 - 11,390'-11,2 #2 - 10,600'-10,5 #3 - 9,800'-9,700 #4 - 6,150'-6,050 #5 - 4,850'-4,750 #6 - 1,900'-1,800 #7 - 60'-30' w/ID #8 - 20'-17' w/2 / Following casing str Surface: 13 3/8", 54	NTENTION TO: PLUG AND ABANDO CHANGE PLANS CHANGE CHANS CHANGE CHASS	ON X REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CO CASING TEST AND CO OTHER: and details, and give pertinent dates, inclue Proposal is to aband s "H" cmt and retarder s "H" cmt and retarder i "H" cmt and retarder i S 7,80 nted in well: t of 468'. Cemented w/ ST&C and 32# S-95 set Tailed w/200 sks "PT"	ALTERING CASING G OPNS. PLUG AND ABANDONMENT EMENT JOB ding estimated date of starting any proposed don well by setting the following c in 7 7/8" hole in 8 5/8" csg '8" csg
NOTICE OF II PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING DTHER: 12 Describe Proposed or Completed OF work) SEE RULE 1103. Well drilled as a dr plugs: #1 - 11,390'-11,2 #2 - 10,600'-10,5 #3 - 9,800'-9,700 #4 - 6,150'-6,050 #5 - 4,850'-4,750 #6 - 1,900'-1,800 #7 - 60'-30' w/III #8 - 20'-17' w/2 (Following casing str Surface: 13 3/8", 54 Intermediate: 8 5/8" Lite	NTENTION TO: PLUG AND ABANDO CHANGE PLANS CHANGE CHANS CHANGE CHANS CHANGE CHASS	ON X REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CO CASING TEST AND CO OTHER: and details, and give pertinent dates, inclue or of the constraint dates, inclue or o	ALTERING CASING G OPNS. PLUG AND ABANDONMENT EMENT JOB ding estimated date of starting any proposed don well by setting the following c in 7 7/8" hole in 7 5/8" csg (8" csg 3" csg (450 sks "P" cement + 2% CaCl ₂ .
NOTICE OF II PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed OF work) SEE RULE 1103. Well drilled as a dr plugs: #1 - 11,390'-11,2 #2 - 10,600'-10,5 #3 - 9,800'-9,700 #4 - 6,150'-6,050 #5 - 4,850'-4,750 #6 - 1,900'-1,800 #7 - 60'-30' w/II #8 - 20'-17' w/2 (Following casing str Surface: 13 3/8", 54 Intermediate: 8 5/8" Lite"	NTENTION TO: PLUG AND ABANDO CHANGE PLANS CHANGE ALL CHANGE CHANGE CHANGE CHANGE CHANGE CHANGE CHANGE CHANGE CHANG	ON X REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CO CASING TEST AND CO OTHER: and details, and give pertinent dates, inclue or of the constraint dates, inclue or o	ALTERING CASING G OPNS. PLUG AND ABANDONMENT EMENT JOB ding estimated date of starting any proposed don well by setting the following in 7 7/8" hole in 8 5/8" csg (450 sks "P" cement + 2% CaCl ₂ . at 4800'. Cemented w/1475 sks + 2% CaCl ₂ . Foreman
NOTICE OF II PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed Of work) SEE RULE 1103. Well drilled as a dr plugs: #1 - 11,390'-11,2 #2 - 10,600'-10,5 #3 - 9,800'-9,700 #4 - 6,150'-6,050 #5 - 4,850'-4,750 #6 - 1,900'-1,800 #7 - 60'-30' w/ID #8 - 20'-17' w/2 (Following casing str Surface: 13 3/8", 54 Intermediate: 8 5/8" Lite Lite	NTENTION TO: PLUG AND ABANDO CHANGE PLANS CHANGE CHANGE CHANGE CHANGE CHAN	ON X REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CO OTHER: and details, and give pertinent dates, inclue Proposal is to aband S "H" cmt and retarder "H" cmt and retarder in "H" cmt and retarder in "S 5/8 nted in well: t of 468'. Cemented w/ ST&C and 32# S-95 set Tailed w/200 sks "PT" cmoviedge and belief.	ALTERING CASING G OPNS. PLUG AND ABANDONMENT EMENT JOB ding estimated date of starting any proposed don well by setting the following t in 7 7/8" hole in 7 5/8" csg (450 sks "P" cement + 2% CaCl ₂ . at 4800'. Cemented w/1475 sks + 2% CaCl ₂ .
NOTICE OF II PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed OF work) SEE RULE 1103. Well drilled as a dr plugs: #1 - 11,390'-11,2 #2 - 10,600'-10,5 #3 - 9,800'-9,700 #4 - 6,150'-6,050 #5 - 4,850'-4,750 #6 - 1,900'-1,800 #7 - 60'-30' w/II #8 - 20'-17' w/2 (Following casing str Surface: 13 3/8", 54 Intermediate: 8 5/8" Lite TYPE OR FRINT NAME Dan A. (This space for State Use)	NTENTION TO: PLUG AND ABANDO CHANGE PLANS CHANGE ALL CHANGE CHANGE CHANGE CHANGE CHANGE CHANGE CHANGE CHANGE CHANG	ON X REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CO OTHER: and details, and give pertinent dates, inclue Proposal is to aband S "H" cmt and retarder "H" cmt and retarder in "H" cmt and retarder in "S 5/8 nted in well: t of 468'. Cemented w/ ST&C and 32# S-95 set Tailed w/200 sks "PT" cmoviedge and belief.	ALTERING CASING G OPNS. PLUG AND ABANDONMENT EMENT JOB ding estimated date of starting any proposed don well by setting the following in 7 7/8" hole in 7 5/8" csg (450 sks "P" cement + 2% CaCl ₂ . at 4800'. Cemented w/1475 sks + 2% CaCl ₂ . Foreman