TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT	+	×.				
FO BE 1990, HOAD, NM 88200 DL BOX 2008 WELL APL NO. 20-023-30788 DYDECT 11 FO. Box 2008 20-023-30788 20-023-30788 DYDECT 11 Santa Fe, New Mexico 87504-2088 20-023-30788 20-023-30788 DYDECT 11 Santa Fe, New Mexico 87504-2088 20-023-30788 20-023-30788 DYDECT 11 SumON & FAID Santa Fe, New Mexico 87504-2088 1. Santa TEK FEE DYDECT 12 SumON & FAID Santa Fe, New Mexico 87504-2088 1. Santa Galacter Tek Va-639 (DO NOTUSE THE FORM FOR PROCEASES TO ONLIGH OF TO FEEPORT PUG BAOK TO A The Second A Galacter Name Va-639 1 THE SCHORT ON PROCEASES TO ONLIGH OF TO FEEPORT PUG BAOK TO A The Second A Galacter Name Va-639 1 Attes of FENDETM CONCORDETION I. Santa Galacter Name Va-639 1 Attes of FENDETM Santa Tek Name North I. Lake Name of Winker 1 Mathematic Concord Name Santa Tek Name North I. Lake Name of Winker 1 Santa Tek Schort Name Santa Tek Name North I. Lake Name of Winker 1 Mathematic Name Santa Tek Name Santa Tek Name North	to Appropriate					
POLINER P.O. Box 2083 POLINERTIN Santa Fe, New Mexico 87504-2088 POLINERTIN Santa Fe, New Mexico 87504-2088 Sinder Top, Areais, NM 8210 Sinder Tep of Law DOWNEY DY, NOTICES AND REPORTS ON WELLS VA-639 (DO NOT USE THE MEDIA TO CEES AND REPORTS ON WELLS VA-639 (DO NOT USE THE MEDIA TO CONCALS, ICO PERMAT Pegasus ARN State 1. James Of general Cast (K) 1. James Of general	DISTRICT 1 P.O. Box 1980 Hobbe NM 88240	OIL CONSERVAT	ION DIVISION	·····		
P.O. Drew DD, Aneis, NM BED0 Salid PE, New MEXICO & Y304-2088 1. Ideaue Type of Last DETECTII San OB & Asia, NM FA10 1. Ideaue Type of Last TATE IX DO NOT USE THE SCORE OR DROCOMS TO ORDER OF PUCE TAK TO A DIFFERENT RESERVICE. USE "APPLICATION FOR PERMIT" 1. Use Name or Usi Agreement Name I Type of View View State 9. Laste Name or Usi Agreement Name I Type of View View State 9. Laste Name or Usi Agreement Name I Type of View View State 9. Laste Name or Usi Agreement Name I Type of View View State 9. Read Read or View Vartes PERTOLEUM CORDERTION 4. Well No. 1 3. Address of Operator View State 9. Read Read or View US South 4 Acts State Northoleum CorDord North 9. Read Read To North Vartes PERTOLEUM CORDERTION TO: Varcuum Atoks Morrow, North 1. Use Later N - 660 Res From The South 1. Vartes PERTOLEUM CORDORATION TO: SUBSECUENT REPORT OF 1. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSECUENT REPORT OF PERFORM REMEDIAL WORK PLUG AND ABANCON CAMMENCE DRULLING OPNS. PLUG AND ABANCONMENT	P.O. Box 2088					
Description Control of the second of the	P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexi	co 87504-2088			
VJ-639 VJ-100 EBCH CORPORATION X Mema Coperator VJ-100 EBCH CORPORATION South 410 S VJ-100 EBCH CORPORATION South 410 S OBE Free Tree The South Line and 1980 Except Mark More Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION T	DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			STATE X FEE		
10 Derived Weil PROJECTION FOR TO DEEPEN OR PULSE REAL TO A PULSE BACK TO A PULSE						
Other Pegasus ARN State 2 Name of Openior & Weil No. 3 Addiend Openior & Weil No. 13 Addiend Openior 9. Pod mame of Wilder 105 South 4th St., Artesia, NM 38210 9. Pod mame of Wilder 14 Weil Location 1980 15 South 4th St., Artesia, NM 38210 9. Pod mame of Wilder 16 South 4th St., Artesia, NM 38210 Vacuum Atoka Morrow, North 16 Main 100 105 South 4th St., Artesia, NM 38210 Vacuum Atoka Morrow, North 16 Main 100 105 South 4th St., Artesia, NM 38210 Vacuum Atoka Morrow, North 17 Mein 100 105 South 4th St., Artesia, NM 38210 North 100 18 Morrow, 100 105 South 2th St., Artesia, NM 38210 County 10 Morrow, 100 100 100 100 10 Morrow, 100 NTO: SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK AltERING CASING PULL OR ALTER CASING County and primer deally and primer deally and preprint deal date of suming any proposed 0 THER: Orther, Re-entry X 12 Deember Poposed of Completed Operation (Clearly state all primers dates, scaling stinstand date of starting any preposed C	DIFFERENT RESER (FORM C-1	POSALS TO DRILL OR TO DEEP VOIR. USE "APPLICATION FOR	EN OB BLUG BACK TO A	7. Lease Name or Unit Agreement Name		
Processor Product of the second state of		OTHER				
1 1 1 105 South 4th St., Artesia, NM 88210 9. Pod same or Widei 4. Well Loadion Vacuum Atoka Morrow, North Usit Lear N : 660 Feet From TheSouthLime and _1980 Feet From TheWestLime and _1980 Section 30 Township 165 Rame 35E NMPMLea Commy	2. Name of Operator					
105 South 4th St., Artesia, NM 88210 9. Pod same or Widdat 1 Weil Localize N: 660 Fee From The South Line and 1980 Fee From The West Line Social 30 Township 16.5 Range 35E NMPM Lea County Line Social 30 Township 16.5 Range 35E NMPM Lea County 10. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data Other Data SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE OFILLING OPNS. PLUG AND ABANDON COMMENCE OFILLING OPNS. PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PULL OR ALTER CASING OTHER: COMMENCE OFILLING OPNS. PLUG AND ABANDON REMEDIAL WORK PLUG AND ABANDON PULL OR ALTER CASING OTHER: OTHER: COMMENCE OFILLING OPNS. PLUG AND ABANDON Remedial Work Remedial Work 10 North Proposed or Completed Operations (Clearly state all peristers date: scienting opn opposed Comment of the casing. Intelling the casing opp opposed Gold of the casing. Intelling the casin		TION		a well No.		
1 Weil Lester N: 660 Feet From The South Line and 1980 Feet From The West Line Section 30 Township 165 Range 35E NMPM Lea County 4026' CR 4026' CR CR County 4026' CR 10 Elevation (More white: DF, RKS, RT, GR, etc.) 4026' CR County 4026' CR 11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PEERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS CCMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CS 12 Desche Proposed on Completed Operations (Clearly state all perison desile, including estimated date of starting any proposed work) SEE RULE 1102. CS CS 6-28-97 Ploy out cellar and cut off casing. Install 11'' 5000# starting head. Dig 6-29.97 Moved in nedrigged up pulling unit. Nippled up 11'' X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved i		sia NM 88210		9. Pool name or Wildcat		
Section 30 Township 165 Range 35E NMPM Lea County 10. Elevation (Mow Warker DP, AKB, MY, GR, etc.) 4026' GR 4026' GR 4026' GR 4026' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: OTHER: OTHER: OTHER: X X SIG TEST AND CEMENT JOB OTHER: OTHER: OTHER: OTHER: X X Sig TEST AND CEMENT JOB OTHER: OTHER: OTHER: X X Sig TEST AND CEMENT JOB OTHER: OTHER: OTHER: X X X X 10. Device dor Completed Operations (Clearly state all perimeted datatil, and give perimeted dates giuting and proposed X X X X 10. Tested BOP and manifold to 4000 psi. Noved in reverse equipment. Noloade 2-7/8" drillipe. Prep to spud. 6-22-97 Moved in re-entry equipment. Unloaded 2-7/8" drillipe. Y Y S	4. Well Location					
Nume Lea County 10. Elevation (Show whather DF, RES, RC, acc.) 4026' GR County 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING FULL OR ALTER CASING CHANGE PLUNS CCMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CHANGE PLUNS CCMMENCE DRILLING OPNS. PLUG AND ABANDONMENT VIL OR ALTER CASING CHANGE PLUNS CCMMENCE DRILLING OPNS. PLUG AND ABANDONMENT VIL OR ALTER CASING CHANGE PLUNS CCMMENCE DRILLING OPNS. PLUG AND ABANDONMENT VIL OR ALTER CASING CHANGE PLUNS CCMMENCE DRILLING OPNS. PLUG AND ABANDONMENT 12. Describe Proposed or Completed Operations (Clearly state all periosen data: isclading estimated data of starting any proposed CASING TEST AND CEMENT JOB 0THER: Comode in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# hydra	Unit Letter <u>N</u> : <u>660</u>	Feet From The South	Line and1980	Feet From The West		
10. Literations (Show which DF, RKB, RT, GR, stc.) 10. 4026' GR 4026' GR 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CAMMENCE DRILLING OPNS. PLUG AND ABANDON CAMMENCE DRILLING OPNS. PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PULL OR ALTER CASING COMMENCE DRILLING OPNS. OTHER: OTHER: CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER: Remetry pit. CASING TEST AND CEMENT JOB 6-26-97 - Dig out cellar and cut off casing. Install 11" 5000# starting head. 0000# choke manifold. Tested BOP and manifold to 4000 psi. 6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. 6-28-97 - Neved in re-entry equipment. Unloaded 2-7/8" drillpipe. 6-28-97 - Noved in re-entry equipment. Unloaded 2-7/8" drillpipe. 6-29-97 - Noved in re-entry equipment. Unloaded 2-7/8" drillpipe. 6-29-97 - Noved in re-entry equipment. Unloaded 2-7/8" drillopipe. 6-29-97 - Drilled to 1900 AM 6-28-97. Drilled to 225'.	Section 30	Township 16S	Range 35E	NMPM Lea Courte		
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: OTHER: OTHER: Re-entry X 12. Describe Proposed or Completed Operations (Clearly state all periment datas, including estimated date of starting any proposed 6-26-97 - Dig out cellar and cut off casing. Install 11" 5000# starting head. Dig re-entry pit. 6-27-97 - Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. 6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. 6-28-97 - Revested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled THE The pase for SegNU						
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT DULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT DULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT DULL OR ALTER CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT DULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: Comments Conside the comment of th	11. Check A					
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER: K 12. Describe Proposed or Completed Operations (Clearly state all periment dates, including estimated date of starting any proposed TEST AND CEMENT JOB 6-26-97 Dig out cellar and cut off casing. Install 11" 5000# starting head. Dig Tere-entry pit. 6-27-97 Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. Circulated clean. TIH and tagged at 5663'. Washing down part of retainer under bit. CONTINUED ON NEXT PAGE: Storation at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled Date Heady cartly bat bid information above is proved complete to the best of my knowledge and bid. CONTINUED ON NEXT PAGE: Storational Rusty Klein The Operations Technician Date Theady c						
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: CASING TEST AND CEMENT JOB OTHER: Re-entry X 12. Describe Proposed or Completed Operations (Clearly state all periment details, and give periment dates, including estimated date of starting any proposed work) SEE RULE 1103. K 12. Describe Proposed or Completed Operations (Clearly state all periment details, and give periment dates, including estimated date of starting head. Dig re-entry pit. Figure Periment dates, including estimated date of starting head. Dig re-entry pit. 6-26-97 - Moved in and rigged up pulling unit. Nippled up 11" X 5000# starting head. Dig re-entry equipment. Work) SEE RULE 1103. 6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. 6-29-97 - Re-tested BOP to 4000 psi. TH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. 6-30-97 - Drilled to 1941'. Circulated clean. TH and tagged at 550'. Circulated clean. TH and tagged at 560'. 6-30-97 - Drilled to 6230'. Drilled to 6340'. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated.			1			
PULL OR ALTER CASING COMMENCE DRILING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB OTHER: OTHER: CASING TEST AND CEMENT JOB 12. Describe Proposed or Completed Operations (Clearly state all periment datatils, and give periment datati, including estimated date of staring any proposed YX work) SEE RULE 1103. 6-26-97 - Dig out cellar and cut off casing. Install 11" 5000# starting head. Dig There: 6-27-97 - Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. 6-29-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Frep to spud. 6-29-97 - Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled to 6340'. Washed down and tagged at 10340'. Drilled Mashing down part of retainer under bit. CONTINUED ON NEXT PAGE: Mashing down part of retainer under bit. CONTINUED ON NEXT PAGE: Mashing down part of retainer under bit. CONTINUED ON NEXT PAGE: Mashing down part of retainer under bit. <td< td=""><td></td><td>the second se</td><td></td><td></td></td<>		the second se				
OTHER: OTHER: Re-entry X 12. Describe Proposed or Completed Operations (Clearly state all perinent data); and give perinent data; including estimated date of starting any proposed 6-26-97 - Dig out cellar and cut off casing. Install 11" 5000# starting head. Dig re-entry pit. 6-27-97 - Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. 6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. 6-29-97 - Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 2255. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged at 5663'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled to 8323'. Circulated 1 hour. TIN. Tagged at 10340'. Drilled to 8323'. Circulated 1 hour. TIN. Tagged at 10340'. Drilled to 8323'. Circulated 1 hour. TIN. Tagged at 10340'. Drilled to 8323'. Circulated 1 hour. TIN. Tagged at 10340'. Drilled to 8323'. Circulated 1 hour. TIN. Tagged at 10340'. Drilled to 8324'. ContINUED ON NEXT PACE: Image on preformation above a preformed complete to the test of my thowledge and bdid. Image on the start of the test of my thowledge and bdid. Image on the start o	PULL OR ALTER CASING	Change Plans				
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of staring any proposed (X) 6-26-97 - Dig out cellar and cut off casing. Install 11" 5000# starting head. Dig (6-26-97 - Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. 6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. 6-28-97 - Re-tested BOP to 4000 psi. TH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TH and tagged at 1785'. Drilled to 1941'. Circulated clean. TH and tagged. Drilled from 2991-3035'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated l hour. TIH. Tagged at 10340'. Drilled There or FRMT NAME More Suppressive Configuration Bove is pressive Configuration Bove is the performance and bit. THE APROVED BY		······		_		
6-26-97 - Dig out cellar and cut off casing. Install 11" 5000# starting head. Dig re-entry pit. 6-27-97 - Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. 6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. 6-29-97 - Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8j35'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled Iberdy cently that the unformation above is nos as complete to the best of my toowkedge mat belid. Stonarture TIME TYPE ON FRANT NAME Rusty Klein THE Operations Technician DATE July 8, 1997 THE THE						
G-27-97 Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. G-28-97 Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. G-29-97 Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated l hour. TIH. Tagged at 10340'. Drilled I hereby centry that be information block is put and complete to the best of my twowledge and bid. CONTINUED ON NEXT PAGE: SIONATURE THE Derations Technician DATE TYPE CA FRONT NAME NULLIAMS 'J. 10 107' APROVED BY TILE DATE DATE	 Describe Proposed or Completed Operation work) SEE RULE 1103. 	ns (Clearly state all persinens details,	and give pertinent dates, includi	ing estimated date of starting any proposed		
G-27-97 Moved in and rigged up pulling unit. Nippled up 11" X 5000# hydraulic BOP, 5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. G-28-97 Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. G-29-97 Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated l hour. TIH. Tagged at 10340'. Drilled I hereby centry that be information block is put and complete to the best of my twowledge and bid. CONTINUED ON NEXT PAGE: SIONATURE THE Derations Technician DATE TYPE CA FRONT NAME NULLIAMS 'J. 10 107' APROVED BY TILE DATE DATE	6-26-97 - Dig out cellar	and cut off casing	. Install 11" 50	00# starting head. Dig		
5000# choke manifold. Tested BOP and manifold to 4000 psi. Moved in reverse equipment. 6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. 6-29-97 - Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 823'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled I hereby cently that the information above is prove of complete to the test of my browledge and belict. SIONATURE TIME Mustry Klein TIME Operations Technician DATE July 8, 1997 Childen NALESIC O CONCENS Superior Superior SWILLIAMS Childen NALESIC O CONCENS Superior NALESIC Mathematican Data Structure Superior Structure Mathematican Data Structure Superion Structure	re-entry pit.					
6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe. Prep to spud. 6-29-97 - Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled I hereby certify that the information above is me and complete to the best of my knowledge and beliet. SNONATURE THE Operations Technician DATE July 8, 1997 TYPE OR PRUT NAME Rusty Klein THE Operations Technician DATE July 8, 1997 CIRCU PROVED BY TILE	5000 choke manifold. T	lested BOP and manif	it. Nippled up 1 old to 4000 pei	1" X 5000# hydraulic BOP, Moved in reverse equipment		
6-29-97 - Re-tested BOP to 4000 psi. TIH with 7-7/8" bit and 4-3/4" drill collar. Spudded on surface plug at 10:00 AM 6-28-97. Drilled to 225'. Circulated clean. TIH and tagged at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled I hereby certify that the information above is pre-sed complete to the best of my trowledge and belief. SIONATURE AUGUSTION Rusty Klein THE Operations Technician DATE July 8, 1997 TYPE OM FRINT NAME Rusty Klein THE OPERATIONS TECHNICIAN SOUTH SUBJECT OF STORY SOUTH	6-28-97 - Moved in re-entry equipment. Unloaded 2-7/8" drillpipe, Prep to spud.					
at 1785'. Drilled to 1941'. Circulated clean. TIH and tagged. Drilled from 2991-3035'. Circulated clean. TIH and tagged shoe plug at 4550'. 6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled I hereby certify that the information above is the best of my knowledge and belief. SIONATURE CONTINUED ON NEXT PAGE: TYPE OR PRINT NAME Rusty Klein THE OPERATION TO DE OF OFFIS WILLIAMS CONTINUED ON AL SICCO OF OFFIS WILLIAMS DATE JULY 8, 1997 THE DATE OFFICIENT I JUP CHVISOR	6-29-97 - Re-tested BOP	to 4000 psi. TIH w	ith 7—7/8" bit an	d 4-3/4" drill collar. Spudde		
6-30-97 - Drilled to 4600'. TOOH - metal had bit locked down. Cleaned out bit and TIH. Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief. I hereby certify that the information above is rue and complete to the best of my knowledge and belief	at 1785'. Drilled to 19) AM 6-28-97. Drill)41'. Circulated cl	ed to 225'. Circ ean. TIH and tag	ulated clean. TIH and tagged ged. Drilled from 2991-3035'.		
Drilled cement to 4700'. Drilled cement retainer. Washed down and tagged at 5663'. Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled I hereby certify that the information above is pre set complete to the best of my knowledge and belief. SKONATURE						
Washing down part of retainer under bit. 7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled I hereby certify that the information above is price and complete to the best of my knowledge and belief. I hereby certify that the information above is price and complete to the best of my knowledge and belief. SIGNATURE USTENDE NO. NEXT PAGE: Must y Klein Operations Technician TYPE OR PRINT NAME DATE Chis space for Steer HOMAL SIGNO BY OHOLS WILLIAMIS UST 10 107 APPROVED BY TILE						
7-1-97 - Washed down to 6230'. Drilled to 6340'. Washed down to 6437'. Circulated. TIH. Tagged at 8135'. Drilled to 8323'. Circulated 1 hour. TIH. Tagged at 10340'. Drilled Ihereby certify that the information above is true and complete to the best of my throwiedge and belief. CONTINUED ON NEXT PAGE: SHONATURE Washed down to 6437'. Circulated. TIH. TYPE OR PRINT NAME Rusty Klein TYPE OR PRINT NAME DATE July 8, 1997 THE DATE DATE U. I. O 107 APPROVED BY TILE			carner, washed u	own and tagged at JUUJ .		
I hereby certify that the information above is true and complete to the best of my knowledge and belief. CONTINUED ON NEXT PAGE: SKONATURE USTERNET NAME Operations Technician TYPE OR PRINT NAME Rusty Klein DATE TYPE OR PRINT NAME Rusty Klein THE Operations Telephone no. 505/748-147 (This space for State Herminician Date Store Difference in CUP Environment Store Transmission USE I O 1007 APPROVED BY THE DATE	7-1-97 - Washed down to	6230'. Drilled to				
Interfor Cellify that the information above is the fact complete to the fact of my factorized and cellif. SKONATURE Interformation Date July 8, 1997 TYPE OR PRINT NAME Rusty Klein THE OPERATIONS Technician DATE July 8, 1997 THE OPERATIONS Technician DATE TYPE OR PRINT NAME Rusty Klein THE OPERATIONS TECHNICIAN THE OPERATIONS TECHNICAL SIGNAL SIG						
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147: TELEPHONE NO. 505		of complete to the best of my knowledge at				
(This space for State HOINAL SICKTO BY CHRIS WILLIAMS DISTRICT CORRINGED APPROVED BY DATE		UsT	meTe	chnician DATE July 8, 1997		
	THEORINAL			теlерноне но. 505/748-		
APPROVED BY DATE	(This space for Sigte 1)@INAL GIC **** O BY EISTELOT → CU	CHRIS WILLIAMS FERVISOR		50 10 1997		
CONDITIONS OF APPROVAL, IF ANY:			me	DATE		
	CONDITIONS OF APPEROVAL, IP ANY:			· •		