

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-30879
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator  
Bridge Oil Company, L.P.

3. Address of Operator  
12404 Park Central Drive, Suite 400, Dallas, Texas 75251

4. Well Location  
Unit Letter H : 2310 Feet From The North Line and 660 Feet From The East Line

Section 34 Township 15S Range 35E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3954.9' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-25-91 thru 2-7-91: MIRU Pride Well Service to plug well. TOH with tubing and packer. Set 5-1/2" CIBP @ 11,650'. Spotted 35' cement plug on top of CIBP (witnessed by Ray Smith-NMOCD). Spotted 20sx class "C" cement plug from 9050'-8950'. Spotted 60sx class "C" cement plug from 8211'-7950' (tagged plug @ 7961' - witnessed by Ray Smith, NMOCD). Spotted 30sx class "C" cement plug from 6290'-6190'. Shot casing @ 4764'. Pulled 43 jts. of 5-1/2", 20# and 64 jts. of 5-1/2", 17# casing. Spotted 30sx class "C" cement plug from 4810'-4710' (plug tagged @ 4800' -witnessed by Ray Smith, NMOCD). Spotted additional 35sx class "C" cement plug from 4800'-4710'. Spotted 30sx class "C" cement plug from 1900'-1800'. Cut off wellhead. Spotted 10sx cement to surface. Weld on marker. RDMO.

NOTE: Entire hole was loaded with 10# salt gel between cement plugs. Location will be cleaned and re-seeded and ready for inspection in 3-4 weeks.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE J. Michael Warren TITLE Regulatory Analyst DATE 2-12-91

TYPE OR PRINT NAME J. Michael Warren TELEPHONE NO. (214) 788-3363

(This space for State Use)

APPROVED BY [Signature] TITLE OIL & GAS DATE

CONDITIONS OF APPROVAL, IF ANY: