

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-30939

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Bridge Oil Company, L. P.

3. Address of Operator
12404 Park Central Dr., Ste. 400, Dallas, Texas 75251

4. Well Location
Unit Letter B : 990 Feet From The North Line and 2310 Feet From The East Line

Section 12 Township 16S Range 36E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3868' GR

7. Lease Name or Unit Agreement Name

Kim Harris

8. Well No.

1

9. Pool name or Wildcat
Northeast Lovington-Wolfcamp

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU service unit to plug and abandon as follows: Set CIBP @ $\pm 10,500'$ with 35' cement plug on top of CIBP (uppermost perms at 10,556'). Cut and pull 5 1/2" production casing @ $\pm 10,000'$. Set 100' cement plug across casing stub from 9,950'-10,050', tag plug. Set 100' cement plug from 6,420'-6,520' (top of Glorieta @ 6,470'). Set 100' cement plug across 8 5/8" casing shoe from 4,454'-4,554', tag plug. Set 100' cement plug from 1,744'-1,844' (top of salt @ 1,794'). Set 10 sack cement surface plug. Hole will be filled with 10# salt gel between plugs. Surface location will be cleaned and restored as required.

Ref @ 470 & set plug across surface shoe

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rhonda J. Sutton TITLE Regulatory Coordinator DATE 9/3/93
TYPE OR PRINT NAME Rhonda Sutton 214/788-3371 TELEPHONE NO.

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE SEP 09 1993

CONDITIONS OF APPROVAL, IF ANY:

THE COMMISSION MUST BE NOTIFIED 24
HOURS PRIOR TO THE BEGINNING OF
PLUGGING OPERATIONS FOR THE C-103
TO BE APPROVED.

RECEIVED

SEP 08 1993

OLD HOUSE
OFFICE