

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.	30-025-31001
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	E-1075

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Lea 396 State
2. Name of Operator Hondo Oil & Gas Company	8. Well No. 5
3. Address of Operator P. O. Box 2208, Roswell, NM 88202	9. Pool name or Wildcat Dean Permo Penn
4. Well Location Unit Letter <u>H</u> : <u>1980</u> Feet From The <u>North</u> Line and <u>660</u> Feet From The <u>East</u> Line Section <u>35</u> Township <u>15S</u> Range <u>36E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3852.4' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well @ 8:00 a.m. 10/06/90. Drilled 17 1/2" hole to 1934'. Ran 43 jts. 13 3/8" 54.5# K-55 ST&C, set @ 1934'. Cemented w/ 1210 sx 50/50 Poz + 6% Gel & 2% CaCl + 1/4#/sx Cello Flakes & 420 sx Class "C" 2% CaCl, plug down @ 4:52 a.m. 10/08/90. Circulated 430 sx cmt, bumped plug @ 890 psi. 11 hrs. WOC. Tested BOP to 1400 psi for 30 min. - held okay. Drilled out w/ 12 1/4" bit 10/09/90. TD 12 1/4" hole @ 3 p.m. 10/14/90. Ran 71 jts 8 5/8" 32# S80 ST&C & 43 jts 32# J-55 set @ 4900'. Cemented w/ 1650 sx 50/50 Poz, 8% Gel + 9#/sack salt, tail 250 sx Class "C", circ 205 sx, bumped plug 1875 psi @ 3:45 a.m. 10/15/90. WOC 24 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE E. L. Buttross Jr. TITLE Petroleum Engineer DATE 10/16/90
TYPE OR PRINT NAME E.L. Buttross, Jr. TELEPHONE NO. (505) 625-6732

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

OCT 17 1990

RECEIVED

OCT 17 1980

OCD
HOBBS OFFICE