

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-023-31110
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-1682
7. Lease Name or Unit Agreement Name  Red Hat State Unit
8. Well No. 1
9. Pool name or Wildcat Wildcat

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210

4. Well Location Unit Letter <u>C</u> Lot <u>15</u> : <u>3300</u> Feet From The <u>South</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>2</u> Township <u>16S</u> Range <u>33E</u> NMPM Lea County	10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4192' GR
--	--

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
<b>NOTICE OF INTENTION TO:</b>	<b>SUBSEQUENT REPORT OF:</b>
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <u>Intermediate Casing</u> <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 103 joints 8-5/8" 32# S-80 and J-55 casing, set at 4515' as follows: 10 jts 32# S-80 and 93 jts 8-5/8" 32# J-55. Guide shoe set 4515', float collar set 4471'. Cemented w/500 sx Pacesetter Lite w/5#/sx salt + 1/4# sx Celloseal + 5#/sx Gilsonite (yield 2.04, wt 12.3). Followed w/1400 sx Pacesetter Lite w/5#/sx Salt + 1/4#/sx Celloseal (yield 1.97, wt 12.4). Tail in w/200 sx "C" + 1% CaCl2 (yield 1.32, wt 14.8). PD 4:15 PM 1-26-91. Bumped plug to 1950 psi, float held OK. Circulated 200 sx cement to pit. NU and tested to 1000 psi for 30 minutes. WOC. Drilled out 9:00 PM 1-27-91. WOC 29 hrs. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 2-18-91

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: