

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31578
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-3273
7. Lease Name or Unit Agreement Name Eidson Ranch Unit
8. Well No. 2
9. Pool name or Wildcat Wildcat San Andres
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4243' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter S : 2310 Feet From The South Line and 2310 Feet From The West Line Section 5 Township 16S Range 33E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 26" hole 4:00 PM 4-20-92. Set 40' of 20" conductor and cement to surface. Resumed drilling 14-3/4" hole 3:00 PM 4-21-92. TD 14-3/4" hole 4-23-92. Ran 34 joints 9-5/8" J-55 36# casing set 1490'. Guide shoe set 1490', insert float set 1449'. Cemented w/1225 sx Pacesetter Lite "C" 65/35/6 + 1% CaCl2 + 1/2#/sx Celloseal (yield 1.66, wt 12.9). Tailed in w/200 sx Class "C" + 2% CaCl2 (yield 1.32, wt 14.8). PD 4:45 PM 4-23-92. Bumped plug to 900 psi, float held okay. Circulated 195 sacks. WOC. Drilled out 6:45 PM 4-24-92. WOC 26 hrs. NU and tested to 1000 psi for 30 minutes, OK. Reduced hole to 8-3/4".  
Note: Notified NMOCD, Hobbs, NM, did not witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 5-4-92  
TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)

Orig. Signed by  
Paul [Signature]  
[Signature]

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: