

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-31830
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-9116
7. Lease Name or Unit Agreement Name Earnestine State
8. Well No. 1
9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER
2. Name of Operator Charles B. Gillespie, Jr.
3. Address of Operator P.O. Box 8 Midland, TX 79702

4. Well Location Unit Letter <u>B</u> : <u>990</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>1</u> Township <u>16S</u> Range <u>35E</u> NMMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3978.3' GR, 3996' KB

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/31/92: Drilled 11" hole to 4738'. Ran 112 jts. 8 5/8" 32# J-55 casing set at 4738' KB. Cemented with 550 sx Class "C" 35/65 Poz cement containing 3 lbs/sx salt and 1 lb/sx Gilsonite followed by 200 sx Class "C" cement containing 1% CaCl₂. Plug down at 6:00 p.m. 12/30/92 with 1750# maximum pump pressure. Wait on cement 12 hrs. Ran temperature survey. Top of cement at 2321'. Tested BOP's and 8 5/8" casing to 1500# for 30 minutes, tested okay. Commenced drilling 7 7/8" hole at 8:00 a.m. 12/31/92.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE William R. Crow TITLE Exploration Manager DATE 12/31/92

TYPE OR PRINT NAME William R. Crow TELEPHONE NO. (915) 683-1765

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
APPROVED BY DISTRICT I SUPERVISOR TITLE _____ DATE JAN - 6 1993

CONDITIONS OF APPROVAL, IF ANY: