

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-32291
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Snyder "S" Com
8. Well No. 1
9. Pool name or Wildcat West Lovington Strawn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3970' GR, 3987.5' KB

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator Charles B. Gillespie, Jr.
3. Address of Operator P.O. Box 8 Midland, Texas 79702	4. Well Location Unit Letter L : 1980 Feet From The South Line and 660 Feet From The West Line Section 34 Township 15S Range 35E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3970' GR, 3987.5' KB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/07/93: ZIADRIL, Inc. Rig No. 2 spudded 17 1/2" hole @ 7:15 a.m. 11/06/93. Drilled 17 1/2" hole to 390'. Ran 9 jts. 13 3/8" 48# H-40 casing set at 390' KB. Cemented with 440 sx Class "C" cement containing 2% CaCl₂. Plug down at 2:00 p.m. 11/06/93 with 450# maximum pump pressure. Cement circulated 105 sx. Wait on cement 12 hrs. Tested BOP and 13 3/8" casing to 1000# for 30 minutes, tested okay. Commenced drilling 11" hole at 2:00 a.m. 11/07/93.

I hereby certify that the information above is true and complete to the best of my knowledge and belief

SIGNATURE

William R. Crow

TITLE Exploration Manager

DATE 11/15/93

TYPE OR PRINT NAME

William R. Crow

TELEPHONE NO. (915) 683-176

(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

NOV 22 1993

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: