



RIG 2 9,000' - 16,000'

P.O. Box 1860 • Hobbs, New Mexico 88241 • 505/397-3511 • 800/922-3745

DRAWWORKS

Emsco GB-800 1000 H.P.
Drum: 1½" Lebus grooved
Compound: 2-engine oil bath chain drive
Brake: Hydromatic Parkersburg 46" Double
Satellite Automatic Driller
Duo-O-Matic Crown Block Protector
Totco Weight Indicator

ENGINES

Two 610-H.P. D379TA Caterpillar Diesel.

DERRICK

Pyramid 136' 800,000 lb. rated capacity.

SUBSTRUCTURE

Pyramid 17' high 800,000 lb. rated capacity.

MUD PUMPS

Pump No. 1: Emsco DC700. 700-H.P. with steel fluid end.
4¾" - 7¾" liners, 16" stroke. Compound driven
Pump No. 2: Emsco DB700 - 700-H.P. powered by D379
Caterpillar Diesel.

DRILL STRING

6,500' 4½" Grade E, 20-lb.
9,000' 4½" Grade E, 16.60-lb.
Tool Joints: 4½" XH, 6¾" OD.
Twenty-Seven drillcollars 6½" OD, 2¼" ID.
Twenty-One 8" OD x 2½" ID Drill Collars
Other sized drillpipe and drillcollars available.

BLOWOUT PREVENTERS

One Shaffer LWS hydraulic double 11" x 5,000 p.s.i. One
Hydril 11" x 5,000 p.s.i. Choke manifold 4" x
5,000 p.s.i. flanged connections. Koomey 7-station
accumulator closing unit with remote control.

MUD SYSTEM

Three 30' x 7½' x 6' steel pits with 700-bbl capacity and
one 250-bbl slug pit. Complete low pressure circulating
system, consisting of four submerged mud guns and two
countersunk jets in each pit. System utilizes a 6 x 8
centrifugal pump, powered by diesel.

MUD HOSE

One 8' x 30' Steel Storage House.

COMMUNICATIONS

24-hour direct telephone interconnection through Hobbs
(505/393-1111) or 1-800/922-3745

OTHER EQUIPMENT

BLOCKS. Oilwell 300 Ton

HOOK. BJ 4300 300 Ton

SWIVEL. Oilwell PC-800 300 Ton

ROTARY TABLE. Gardner Denver 27½"

SHALE SHAKER. Totco Double Screen.

ELECTRICAL POWER. One 210-kw/one 90-kw AC
generators powered by diesel engines. AC fluorescent or
mercury vapor lights. All vapor-proof.

FRESH WATER STORAGE. Two 500-bbl horizontal tanks.

HOUSING. One 10' x 44' refrigerated air-conditioned
house with sleeping and cooking facilities.

