

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088

Santa Fe, New Mexico 87504-2088

CONFIDENTIAL

Form C-105
Revised 1-1-89

WELL API NO.	30-025-32852
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG	
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐	7. Lease Name or Unit Agreement Name Klein Fee
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER ☐	8. Well No. 1

2. Name of Operator Charles B. Gillespie, Jr.	9. Pool name or Wildcat West Lovington Strawn
3. Address of Operator P. O. Box 8 Midland, TX 79702	

4. Well Location Unit Letter B : 760 Feet From The North Line and 2090 Feet From The East Line Section 33 Township 15-S Range 35-E NMPM Lea County
--

10. Date Spudded 2-15-95	11. Date T.D. Reached 3-17-95	12. Date Compl. (Ready to Prod.) 3-31-95	13. Elevations (DF & RKB, RT, GR, etc.) 3981' GR	14. Elev. Casinghead 3981' GR
-----------------------------	----------------------------------	---	---	----------------------------------

15. Total Depth 11,935'	16. Plug Back T.D. 11,796'	17. If Multiple Compl. How Many Zones? XX	18. Intervals Drilled By Rotary Tools Cable Tools
----------------------------	-------------------------------	--	---

19. Producing Interval(s), of this completion - Top, Bottom, Name 11,572-11,582', Strawn	20. Was Directional Survey Made Yes
---	--

21. Type Electric and Other Logs Run BHCSL, DLL/MSFL, LDT/CNL	22. Was Well Cored No
--	--------------------------

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB/FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13-3/8"	48	405'	17-1/2"	440 sx "C"	--
8-5/8"	32	4,698'	11"	700 sx "C"	--
5-1/2"	17	11,935'	7-7/8"	600 sx "H"	--

24. TUBING RECORD	25. TUBING RECORD
SIZE TOP BOTTOM SACKS CEMENT SCREEN	SIZE DEPTH SET PACKER SET
	2-7/8" 11,582' 11,493'

26. Perforation record (interval, size, and number) 11,572-11,582' 2 spf, 21 holes	27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED Natural
--	--

28. PRODUCTION

Date First Production 3-31-95	Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing	Well Status (Prod. or Shut-in) SI				
Date of Test 3-31-95	Hours Tested 6	Choke Size 18/64"	Prod'n For Test Period Oil - Bbl. 114	Gas - MCF 136	Water - Bbl. 0	Gas - Oil Ratio 1193
Flow Tubing Press. 650#	Casing Pressure Packer	Calculated 24-Hour Rate 456	Oil - Bbl. 544	Gas - MCF 0	Water - Bbl. 46	Oil Gravity - API - (Corr.)

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Vented	Test Witnessed By Albert Hobbs
--	-----------------------------------

30. List Attachments Electric logs, Deviation surveys
--

31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief

Signature Kevin Widner Printed Name Kevin Widner Title Production Mgr. Date 4-3-95

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	1,860'	T. Canyon	
T. Salt	1,960'	T. Strawn	11,556'
B. Salt	2,998'	T. Atoka	11,822'
T. Yates	3,025'	T. Miss	
T. 7 Rivers		T. Devonian	
T. Queen	3,868'	T. Silurian	
T. Grayburg		T. Montoya	
T. San Andres	4,659'	T. Simpson	
T. Glorieta	6,516'	T. McKee	
T. Paddock		T. Ellenburger	
T. Blinbry		T. Gr. Wash	
T. Tubb	7,404'	T. Delaware Sand	
T. Drinkard		T. Bone Springs	
T. Abo	8,120'	T.	
T. Wolfcamp	9,714'	T.	
T. Penn	10,866'	T.	
T. Cisco (Bough C)		T.	

Northwestern New Mexico

T. Ojo Alamo		T. Penn. "B"	
T. Kirtland-Fruitland		T. Penn. "C"	
T. Pictured Cliffs		T. Penn. "D"	
T. Cliff House		T. Leadville	
T. Menefee		T. Madison	
T. Point Lookout		T. Elbert	
T. Mancos		T. McCracken	
T. Gallup		T. Ignacio Otzte	
Base Greenhorn		T. Granite	
T. Dakota		T.	
T. Morrison		T.	
T. Todilto		T.	
T. Entrada		T.	
T. Wingate		T.	
T. Chinle		T.	
T. Permian		T.	
T. Penn "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from 11,572' to 11,622' No. 3, from _____ to _____
 No. 2, from _____ to _____ No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
0'	390'	390'	Sand, gravel & caliche	9714'	10024'	310'	Limestone
390'	1860'	1470'	Redbeds	10024'	10633'	609'	Limestone & shale
1860'	1960'	100'	Anhydrite	10633'	10866'	233'	Limestone & chert
1960'	2998'	1038'	Salt & anhydrite	10866'	11556'	690'	Shale & limestone
2998'	3025'	27'	Anhydrite	11556'	11774'	218'	Limestone
3025'	3277'	252'	Sand, dolomite & anhydrite	11774'	11822'	48'	Sand, limestone & shale
3277'	3868'	591'	Dolomite, anhydrite & sand	11822'	11935'	113'	Shale
3868'	4303'	435'	Sand, dolomite & anhydrite				
4303'	4659'	356'	Dolomite & anhydrite				
4659'	6516'	1857'	Dolomite				
6516'	6820'	304'	Sand & dolomite				
6820'	7404'	584'	Dolomite				
7404'	7671'	267'	Sand & dolomite				
7671'	8120'	449'	Dolomite				
8120'	8630'	510'	Dolomite & shale				
8630'	9208'	578'	Dolomite				
9208'	9539'	331'	Dolomite & shale				
9539'	9714'	175'	Dolomite				