INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, vertical depth shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is filed in quintuplicate except on state land, where six copies are requested. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico			No	Northwestern New Mexico	
T. Anhy	1390'	T. Canyon	T. Ojo Alamo	T. Penn "B"	
T. Salt	1513'	T. Strawn	T. Kirtland Fruitland		
B. Salt	2483'	T. Atoka	T. Dietured Cliffe	T. Penn *D*	
T. Yates	2704'	T. Miss	T. Cliff House	T. Leadville	
T. 7 Rivers	3047	T. Devonian	T. Menefee	T. Madison	
T. Queen	3684'	T. Silurian	T. Daint Laakaut	T. Eibert	
T. Grayburg	4108'	T. Montoya	T. Mancos	T. McCracken	
T. San Andres	4428'	T. Simpson	T. Gallup	T. Ignacio Otzte	
T. Glorieta		T. McKee	D. O	T. Granite	
T. Paddock		T. Ellenburger	T. Dakota	T.	
T. Blinebry		T. Gr. Wash	T Marriage	т	
T. Tubb		T. Delaware Sand	T. Todilto	т.	
T. Drinkard		T. Bone Springs	T. Entrada	T.	
T. Abo		т.	T. Wingate	T.	
T. Wolfcamp		т.	T. Chinle	T.	
T. Penn		τ.	T. Permain	T.	
T. Cisco (Bough C)		Т	T. Penn "A"	т.	
		OIL OR G	GAS SANDS OR ZONES		
No. 1. from		to	No. 3, from	to	
No. 2, from					
		IMPOR	TANT WATER SANDS		
include data on rate	of water inflow	and elevation to which water rose in h	nole.		
No. 1, from		to		feet	
				feet	

From	То	Thickness in Feet	Lithology
0	300	300	Caliche & Sand
300	650	350	Red sand, shale
650	1390	740	Red Beds
1390	1513	123	Anhydrite
1513	2483	970	Salt
2493	4950	2457	Dolomite, Salt,
			Anhydrite

From	То	Thickness in Feet	Lithology
	•		
		ļ	