Submit 3 Copies to Appropriate District Office

#### State of New Mexico Energy, Minerals & Natural Resources Department

DISTRICT I	<b>OIL CONSERVATION DIV</b>	<b>ISION</b>	WELL API NO.
P. O. Box 1980, Hobbs, NM 88240	P. O. Box 2088		30-025-33143
<u>DISTRICT II</u> P. O. Drawer DD, Artesia, NM 88210	Santa Fe, NM 87504-2088		5. Indicate Type of Lease STATE FEE
DISTRICT III		ſ	6. State Oil & Gas Lease No.
1000 Rio Brazos Rd., Aztec, NM 87410			B-2148
	ES AND REPORTS ON WELLS		
DIFFERENT RESERVO (FORM C-1)	DSALS TO DRILL OR TO DEEPEN OR PLUG BA DIR, USE "APPLICATION FOR PERMIT" 01) FOR SUCH PROPOSALS.)	СК ТО А	7. Lease Name or Unit Agreement Name Maljamar Grayburg Unit
1 Type of Well:			
OIL GAS WELL WELL	OTHER Water Injection	n Well	
2. Name of Operator			8. Well No.
The Wiser Oil Co	ompany		152
3. Address of Operator			9. Pool name or Wildcat
P.O. Box 2568	Hobbs, New Mexico 88241		Maljamar Grayburg San Andres
	Feet From The <u>North</u> Line and Township <u>17S</u> Range 321	E NMP	_
	10. Elevation (Show whether DF, RKB, RT, 4164' GR		
	Appropriate Box to Indicate Nature of	f Notice, Rep	port, or Other Data
NOTICE OF INTE	NTION TO	SUBSE	QUENT REPORT OF:
		LWORK	
TEMPORARILY ABANDON		CE DRILLING C	PNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TE	EST AND CEME	
OTHER:	OTHER:	Spudding, Cer	nenting Surface & Production Casing

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

MIRU Norton Drilling Co., Rig # 7. Spudded 12-1/4" hole @ 2:15 p.m. 03/12/97. Drilled hole to 365'. Ran 8 jts. 8-5/8", 23#, ISW-42, ST&C csg. Set at 364'. Halliburton cemented with 325 sx. Class "C" containing 1/4#/sk. Flocele + 2% CaCl. Plug down @ 9:00 p.m. 03/12/97. Circulated 85 sx. cmt. BLM & OCD were notified to witness intent of cmt. & csg. No representative present. NU BOP & tested csg. to 1000# for 30 minutes, no pressure loss. WOC 12 hrs,

Drilled 7-7/8" production hole to a depth of 4250'. Ran 104 jts. 5-1/2",17#, J-55 LT&C csg. Set at 4250'. Halliburton cemented w/1000 gals. Superflush 102 + 750 sx. Halliburton Lite with 8# salt/sk + 1/4# flocele/sk. followed by 250 sx. Premium Plus with 3# KCL/sk. + .5% Halad 344 + 1/4# flocele/sk. Displaced w/1 bbl. FW + 12 bbls. MSA + 85 bbls. FW w/Lo-Surf 300. Plug down at 7:45 p.m. 03/17/97. Circ. 117 sx. cmt. Pressure tested casing to 1500# for 30 minutes, no pressure loss. Released rig at 9:45 a.m. 03/17/97

I hereby certify that the information above is true and complete to the best of my knowledge a	nd belief.	
signature Jo Tuinin	TITLE Drilling Department	DATE <u>March 22, 1997</u>
TYPE OR PRINT NAME; Mary Jo Turner		TELEPHONE NO. (505) 392-9797
の「日本の「発生」「発生」「変要要的」「変要要的」」であった。 「「日本のの」」の目的に、「日本の」」では、		MAY 0 2 1997

## **INSTRUCTIONS**

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

# INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

#### Southeastern New Mexico

## Northwestern New Mexico

T. Anhy	2192' 2372' 2645' 3304' 3680' 4060'	T. Canyon T. Strawn T. Atoka T. Miss T. Devonian T. Silurian T. Silurian T. Montoya T. Montoya T. Simpson T. McKee T. Ellenburger T. Gr. Wash T. Delaware Sand T. Bone Springs	T. Pictured Cliffs T. Cliff House T. Menefee T. Point Lookout T. Mancos T. Gallup	T. Penn. "B"
T. Abo		T T T T	T. Wingate T. Chinle T. Permain T. Penn "A"	T T T

## OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 3, from to	
No. 2, from	to	No. 4, from to	•••••••••••••••••••••••••••••
	111000		
Include data on rate of wate	r inflow and elevation to which water	rose in hole.	
NO. 1, HOIII	to	feet	
No. 2, from	to		
No. 3, from	to		•••••
			•••••

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	То	Thickness in Feet	Lithology	From	То	Thickness in Feet	Lithology