Submit 3 copies to Appropriate District Office

(THIS SPACE FOR STATE USE)

CONDITIONS OF APPROVAL, IF ANY:

APPROVED BY

ORIGINAL STONED BY MILE ______
FIELD ...

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

JUN 26 1996

DATE

OIL CONSERVATION DIVISION

DISTRICT I	310 Old Santa Fe Trail, Room 206 Santa Fe, New Mexico 87503	WELL APINO. 33271
P.O. Box 1980, Hobbs, NM 88240	Dalita 1 6, 116W Michieu 67303	
DISTRICT_II P.O. Box Drawer DD, Artesia, NM 88210 DISTRICT_III 5. Indicate Type of Lease STATE X FEE 6. State Oil & Gas Lease No.		
DISTRICT_III		6. State Oil & Gas Lease No. B-2148
1000 Rio Brazos Rd., Aztec, NM 8	7410	D-2140
SUNDRY N	OTICES AND REPORTS ON WELLS I FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	
DIFFERENT	RESERVOIR USE "APPLICATION FOR PERMIT" 01)FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name Caprock Maljamar Unit
1. Type of Well:		Capiock Marjania One
Oil X Gas	OTHER	
Well Well 2. Name of Operator		8. Well No.
	: Wiser Oil Company	9. Pool name or Wildcat
3. Address of Operator 811	5 Preston Road, Suite 400, Dallas, TX 75225	Maljamar Grayburg San Andres
4. Well Location	• 1330 Feet From The South Line and 1305 Feet From Th	ne East Line
Unit Letter I	: 1330 Feet From The South Line and 1305 Feet From Th	<u> </u>
Section 20	Township 17S Range 33E NMPM	County Lea
	10. Elevation (Show whether DF, RKB, GR, etc.) 4189' GR	
11.	Check Appropriate Box to Indicate Nature of Notice, Report, or Other I	Oata Oata
	NTENTION TO: SUBSEQUENT REP	ORT OF:
PERFORM REMEDIAL WOR		ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CASING TEST AND CEMENT JOB	B [_]
OTHER:	OTHER: Perf & acidize	X
12. Descibe Proposed or Comple SEE RULE 1103.	eted Operation (Clearly state all pertinent details, and give pertinent dates, including estimated	date of starting any proposed work)
03/08/96	Perforate 4527, 28, 29, 30, 31, 32, 33, 34, 35 (9 holes) Acidize perfs 4527-	4535' w/15,000 gals 15% NEFE acid.
03/12/96	Perforate 4442-4455' and 4460-4465'. Acidize perfs 4442-4465' w/ 15,000 g	gals 15% NEFE acid.
03/14/96	Run 2 7/8" tbg. SN set @ 4550.	
03/15/96	Ran 2½" x 1-1/2" x 20' pump.	
I hereby certify that the information at	hove is true an complete to the best of my knowledge and belief.	
SIGNATURE	Setty Esie TILE Production Administrator	DATE 06/19/96
TYPE OR PRINT NAME B	etty Epie	TELEPHONE NO. (214)265-0080