

DISTRICT I

P. O. Box 1980, Hobbs, NM 88240

DISTRICT II

P. O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P. O. Box 2088
Santa Fe, NM 87504-2088

WELL API NO.

30-025-33281

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

B-2148

7. Lease Name or Unit Agreement Name

Caprock Maljamar Unit

8. Well No.

210

9. Pool name or Wildcat

Maljamar Grayburg San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL

WELL ☒

GAS

WELL ☐

OTHER

2. Name of Operator

The Wiser Oil Company

3. Address of Operator

P.O. Box 2568 Hobbs, New Mexico 88241 (505) 392-9797

4. Well Location

Unit Letter O : 1141 Feet From The South Line and 2472 Feet From The East Line

Section 20 Township 17S Range 33E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4087' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Convert & acidize ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/14/98 MIRU Pool Well Service. ND WH. POH w/rods & pump. RU BOP. POH w/2-7/8" tbg. LD TAC & BHA. RIH w/4-3/4" bit & scraper on 2-7/8" tbg. to 4665'. POH w/2-7/8" tbg. LD bit & scraper.

9/15/98 RIH w/5-1/2" R-4 pkr. on 2-7/8" tbg. to 4150'. RU Reef Chemical & spot scale converter across perf. interval. RD reef. Left to soak.

9/16/98 Set pkr. @ 4150'. Drop standing valve & pressure test tbg. to 3500#. Held. Fish standing valve. RU Reef Chemical & acidize Grayburg Vacuum & Jackson 4179'-4637' w/2000 gals. 15% anti-sludge acid w/20 ball sealers. Good ball action. ATP 2000# @ 4.0 bpm. MTP 2650# @ 4.4 bpm. ISIP 2000#. 5 min. 950#. 10 min. 450#. 15 min. 200#. Flush w/35 bbls. fresh water. RD Reef. POH w/tbg. LD pkr. RIH w/2-7/8" tbg. Tbg. @ 4179'. SN @ 4144'. RD BOP. RIH w/rods & 2-1/2" x 2" x 20' pump. NU WH. Left well pumping to Battery "A".

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mary Jo Turner TITLE Production Tech II DATE October 18, 2001

TYPE OR PRINT NAME Mary Jo Turner

(This space for State Use)

APPROVED BY

TITLE

DATE

ORIGINAL FILED BY
PAUL E. HARRIS
OCT 19 2001