



P.O. Box 552  
Midland, Texas 79702  
Telephone 915/682-1626

J.M. DENTON #14  
1650' FSL & 2275' FEL  
SEC. 11, T-15-S, R-37-E  
LEA CO., NEW MEXICO

2/17/96 - MIRU TMBR/SHARP #27. SPUD 17-1/2" HOLE @ 0815 HRS. DRILLED 17-1/2" HOLE TO 390'. RAN 9 JTS 13-3/8", 48#, H-40, STC CSG TO 390', FLOAT SHOE @ 388', FLOAT COLLAR @ 343'. CEMENTED SURFACE CASING W/400 SX PREMIUM PLUS W/2% CACL<sub>2</sub>, CIRCULATED 80 SX TO SURFACE. CUT CASING INSTALLED 13-3/8" 3M SOW CSG. HEAD. TESTED WELD TO 1000 PSI.

NIPPLED UP 13-5/8"-5M DUAL RAM BOPE'S. TESTED CHOKE MANIFOLD, CHOKE AND KILL LINES, BLIND AND PIPE RAMS, SURFACE LINES AND FLOOR VALVES TO 500/3000 PSI. TIH W/12-1/4" BIT & TAGGED CMT @ 322'. TOTAL WOC - 28 HRS. TESTED CSG TO 1000 PSI. DRILLED FLOAT COLLAR & CEMENT TO 365'. TESTED CSG. TO 1000 PSI. DRILLED CEMENT, SHOE & FORMATION TO 398'. RAN P.I.T. TO 12 PPG EMW.

DRILLED 12-1/4" HOLE TO 4783' TD @ 0845 HRS 2/27/96.

RAN 109 JTS 9-5/8", 36#, K-55, STC TO 4783', FLOAT SHOE @ 4782',  
COLLAR @ 4709'. , FLOAT

CEMENTED INTERMEDIATE CASING W/1080 SX HOWCO 'LITE' W/12 PPS NACL, .25 PPS FLOCELE, WT-12.49 YIELD 2.21, TAILED IN W/500 SX PREMIUM PLUS W/.2% ECONOLITE WT - 14.8, YIELD - 1.32. BUMPED PLUG @ 0600 HRS 2/28/96, CIRC'D 25 SX TO SURFACE SET SLIPS, N.U. 13-5/8" 5M X 11" 5M 'B' SECTION, TESTED SEALS TO 1500 PSI. N.U. 13-5/8" 5M DUAL RAM BOPE'S. TESTED BLIND AND PIPE RAMS, SURFACE LINES, FLOOR VALVES AND SURFACE LINES, CHOKE AND KILL LINES AND MANIFOLD TO 200/5000 PSI.

TOTAL WOC - 26 HRS. TIH & TAG CEMENT @ 4678'. TEST CSG TO 1000 PSI. DRILL PLUG & FLOAT TO 4763'. TEST CSG TO 1000 PSI. DRILL FORMATION TO 4793'. RAN P.I.T. TO 10 PPG EMW.

RESUMED DRLG FORMATION W/8-3/4" BIT.

G:\MIDOPS\SEGROUP\WJD\JMDEN14.WPD