Form 3160-5 (November 1983) (Formerly 9-331)	UNITEI TATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		NsMaxOil Consct. 9 R P.O. Box (1999) Hobbs, NM 88241	Sion Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO.
	_			NM-0315712
	t use this form for prop	CES AND REPORTS C osals to drill or to deepen or plug back to ATION FOR PERMIT - " for such prop	a different reservoir.	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
1.	Use APPLIC	ATION FOR FERMIT - To such prop	08415.)	7. UNIT AGREEMENT NAME
OIL GAS OTHER WELL OTHER				Maljamar Grayburg Unit
2. NAME OF OPERATOR The Wiser Oil Company				8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR				9. WELL NO.
P. O. Box 2568 Hobbs, New Mexico 88241				100
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) 				10. FIELD AND POOL, OR WILDCAT Maljamar Grayburg San Andres
At surface 377' FSL & 1667' FWL Sec. 4-T17S-R32E Unit N				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 4-T17S-R32E
14. PERMIT NO		15. ELEVATIONS (Show whether DF 4109.7'	r, RT, GR, etc.)	12. COUNTY OR PARISH13. STATHLea Co.NM
<u>.</u>	Check A	ppropriate Box to indicate Nati	ure of Notice, Report, or Otl	
				UBSEQUENT REPORT OF
TEST WATER SHU	JT OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	r 🚽	MULTIPLE COMPLETE	FRACTURE TREATMENT	
SHOOT OR ACIDIZ		ABANDON*	SHOOTING OR ACIDIZIN	NG ABANDONMENT
REPAIR WELL		CHANGE PLANS	(Other) Spudding, Cen	nenting, Surface & Production Casing
				s of multiple completion on Well tes, including estimated date of starting any
proposed work. 1 MIRU Norton 9 jts. 8-5/8", 2	f well is directionally Drilling Co., R 23#, K-55 LT&	trilled, give subsurface locations and meaning #5. Spudded 12-1/4" surface csg. Set at 449'. Hallibus	asured and true vertical depths for all ace hole @ 3:15 p.m., 07, rton cemented with 325 sx	 I markers and zones pertinent to this work.) /20/96. Drilled hole to 449'. Ran Class "C" containing 1/4#/sk. BLM was notified, no representative
		sg. to 1000# for 30 minutes, 1		
LT&C csg. 8# salt/sk. + Displaced w/	Set at 4450'. H 1/4# flocele/sk. /1 bbl. FW + 12 pressure loss. Pl	falliburton cemented w/1000 followed by 250 sx. Premiu bbls. MSA + 90 bbls. KCL v	gals. Superflush 102 + 11 m Plus + 3#KCL/sk. + .5 ⁶ water. Circ. 110 sx. cmt.	ing. Ran 106 jts. <u>5-1/2</u> " 17#, J-55 00 sx. Halliburton Lite + % Halad 344 + 1/4# flocele/sk. Pressure tested casing to 1500# for 30 n.m. 07/27/96. BLM was notified,
8 I hereby certify that	the foregoing is true a	nd correct.	·····	
signed <u>Maa</u>	4 Jo Tuenen	TITLE Drilling	g Department	DATE July 30, 1996
(This space for Federa	al or State office use)			
APPROVED BY CONDITIONS OF A	PPROVAL, IF ANY:	TITLE		ACCEPTED FOR RECORD
		*See Instruct	ion On Reverse Side	AUG 2 8 1996
Title 18 U.S.C. Section tatements or represented	1001, makes it a crim ations as to any matter	e for any person knowingly and willfully within its jurisdiction.	to make to any department or agend	cy of the United States any false, fictitious or fraudulent