

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-33466
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name "SV" Chipshot
8. Well No. 1
9. Pool name or Wildcat Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER	2. Name of Operator Manzano Oil Corporation 505/623-1996
3. Address of Operator P.O. Box 2107/Roswell, NM 88202-2107	4. Well Location Unit Letter <u>K</u> : <u>2164</u> Feet From The <u>South</u> Line and <u>1362</u> Feet From The <u>West</u> Line Section <u>11</u> Township <u>16 South</u> Range <u>36 East</u> NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3886'	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/09/96 Spud well @ 3:00 p.m. 6/8/96. Ran 12 jts 13-3/8" 48#, 54# & 61# csg. Set @ 414'KB. Cemented w/350 sks Class C. Circ 30 sks to pit.
6/18/96 TD 4352'. Ran 107 jts 8-5/8" 32# HCK & K55 csg. Set @ 4352'. Cemented w/1600 sks of 35% Poz/65% C. Tail in w/200 sks Class C + 2% CaCl. Circ 270 sks to pit.
7/05/96 DST Wolfcamp interval 10,550-10,605' = 55'. Reverse out 31.1 bbls 39° API gravity oil.
7/13/96 TD 11,954'. Run 282 jts 5-1/2" 17# & 20# csg w/float shoe, float collar, DV tool @ 7051'. Set @ 11,954'. Cement 1st stage w/530 sks Class H. Pump 2nd stage of cement - 350 sks of lite. Tail in w/100 sks C Neat.
7/25/96 Run CBL. TOC 9430'. TOC (2nd stage) 4720'.
7/27/96 Perf Strawn 11,528-44' = 16'.

OVER

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Allison Hernandez TITLE Engineering Technician DATE 8/14/96

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

AUG 16 1996

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: