

# INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy _____	1807	T. Canyon _____	11000
T. Salt _____	1960	T. Kirtland-Fruitland _____	
B. Salt _____		T. Pictured Cliffs _____	
T. Yates _____	2989	T. Cliff House _____	
T. 7 Rivers _____		T. Menefee _____	
T. Queen _____	3818	T. Point Lookout _____	
T. Grayburg _____	4243	T. Mancos _____	
T. San Andres _____	4568	T. Gallup _____	
T. Glorieta _____	6242	Base Greenhorn _____	
T. Paddock _____		T. Dakota _____	
T. Blinebry _____		T. Morrison _____	
T. Tubb _____	7330	T. Todilto _____	
T. Drinkard _____	7600	T. Entrada _____	
T. Abol _____		T. Wingate _____	
T. Wolfcamp _____	9688	T. Chinle _____	
T. Penn _____	10761	T. Permian _____	
T. Cisco (Bough C) _____	10912	T. Penn "A" _____	

### OIL OR GAS SANDS OR ZONES

No. 1, from ..... to ..... No. 3, from ..... to .....  
 No. 2, from ..... to ..... No. 4, from ..... to .....

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from ..... to ..... feet .....  
 No. 2, from ..... to ..... feet .....  
 No. 3, from ..... to ..... feet .....

### LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
			(Continued from the front)				
		DEPTH 10,267-10,278'	ACID SHOT. FRACTURE 2500 gals of 15% HCL,				