

DISTRICT I

P. O. Box 1980, Hobbs, NM 88240

DISTRICT II

P. O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P. O. Box 2088
Santa Fe, NM 87504-2088

WELL API NO.
30-025-34063

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name
Maljamar Grayburg Unit

8. Well No.

127

9. Pool name or Wildcat

Maljamar Grayburg San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1 Type of Well:

OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator

The Wiser Oil Company

3. Address of Operator

P.O. Box 2568 Hobbs, New Mexico 88241 (505) 392-9797

4. Well Location

Unit Letter D : 660 Feet From The North Line and 660 Feet From The West Line
Section 4 Township 17S Range 32E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4162'

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Re-perf. & acidize Grayburg ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/17/98 MIRU Pool Well Service. Pump stuck. Backed off @ rods & swab tbg. POH w/rods. ND WH. RU BOP. POH w/2-7/8" tbg. LD BHA. Halliburton perforate Grayburg 3862', 63', 64', 77', 97', 3903', 04', 05', 19', 20', 27', 28', 32', 46', 53', 54', 55', 96', 97', 98', 4007', 14', 15', 18', 19', 21' & 22' w/4 SPF. RD WL. RIH w/1 jt. 2-3/8" tail pipe, AD-1 pkr. & 122 jts. 2-7/8" tbg. Pkr. @ 3842'. Tail pipe @ 3875'.

8/18/98 Halliburton acidized Grayburg 3862'-4022' w/2400 gals. pad acid w/Toluene in 4 stages w/2000# rock salt in 3 stages. Flush @ 2000# tbg. & 1800# csg. ATP 2150# @ 4.5 bpm. MTP 2580# @ 6.2 bpm. RD HWS. SI 1 hr. Csg. 45#. POH w/tbg. LD pkr. RU testers testing 2-7/8" tbg. 5000# under slips. Found 4 bad jts. RD testers. RD BOP. NU WH. RIH w/rods & 2-1/2" x 1-1/2" x 16' pump. Load & test to 500#. Left well pumping to Battery.

I hereby prtfy that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mary Jo Turner TITLE Production Tech II DATE August 30, 2001

TYPE OR PRINT NAME Mary Jo Turner

(This space for State Use)

APPROVED BY

TITLE Production Tech II DATE Aug 30 2001

CONDITIONS OF APPROVAL, IF ANY: