## **INSTRUCTIONS**

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-dr or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all sp tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is a filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

## INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STAT

Southeastern New Mexico		Northwe	Northwestern New Mexico		
1. Anhy	Т. Сапуоп	T. Oio Alamo	T Done "D"		
2. on	I. Atoka	I. Pictured Cliffs	T Donn "To"		
	I. NIISS		Tlenduille		
	I. Devonian	T. Menefee	T Mullings		
	T. Silurian	T. Point Lookout	T Elbert		
.) our <u>g</u>		T Managa			
		T. Gallun	T 1		
	I. Chenburger	1 123800	T T		
		I NOTISON			
	I. Delaware Sand	L. Lotillo	T		
1. Diukalu	I. Bone Springs	- http://p	T		
		L V Incate	7		
		L Chinle	I		
T. Penn	T	T. Permain	1		
T. Cisco (Bough C)	T.	T. Penn "A"	T 		
		AS SANDS OR ZONES			
No 2 from		No. 3, from	••••••••••••••••••••••••••••••••••••••		
	••••••••••••••••••••••••••••••••••••••	No. 4, Irom	to		
Include data on rate of wate		ANT WATER SANDS			
No 1 from	r inflow and elevation to which w	ater rose in hole.			
No 2 from		feet	• • • • • • • • • • • • • • • • • • • •		
No 3 from		feet	•••••••••••••••••••••••••••••••••••••••		
110. J, IIUIII	•••••••••••••••••••••••••••••••••••••••				

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	То	Thickness in Feet	Lithology	Frem	 ٦٥	Thickness in Feet	Lithology
0 300 1420 1610 2560 2755	300 1420 1610 2560 2755 4950	300 1120 190 950 195 2195	Surface sand, gravel Red Beds Anhydrite Salt Anhydrite & Lime Dolomite & Anhydrite w/Sand Stringers	clay			PEN 2/13/98