

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-34159
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Lazarus ARV
8. Well No.	1
9. Pool name or Wildcat	Garrett Drinkard

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter <u>H</u> : <u>2100</u> Feet From The <u>North</u> Line and <u>990</u> Feet From The <u>East</u> Line Section <u>30</u> Township <u>16S</u> Range <u>38E</u> NMPM Lea County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) <u>3742' GR</u>	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PLUG AND ABANDONMENT <input checked="" type="checkbox"/> ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ken Collins, consultant for Yates Petroleum Corporation received plugging orders from Buddy Hill w/OCD-Hobbs. Plugged and abandoned well as follows:

TD 8800'; PBTD 8520'. Plugs set as follows:

Plug #1: 30 sacks Class "C" set at 6500'. Laid down 60 joints drillpipe.
Plug #2: 60 sacks Class C with 2% CaCl2 set at 4550'. Pulled 8 stands. WOC.
Tagged plug at 4325'. Laid down drillpipe.
Plug #3: 30 sacks Class C with 2% CaCl2 set at 2250'. Laid down drillpipe.
Plug #4: 30 sacks Class C with 2% CaCl2 set at 410'. Nippled down BOP and cut off head.
Plug #5: 10 sacks Class C at surface.

Released rig at 3:45 PM 11-17-97. Installed regulation abandonment marker. PLUGGED AND ABANDONED - FINAL REPORT. Plugging completed 11-17-97.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 22, 1997
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY
GARY WINK
FIELD REP. II

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

105

DP