

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-34159
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Lazarus ARV
8. Well No. 1
9. Pool name or Wildcat Garrett Drinkard

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter <u>H</u> : <u>2100</u> Feet From The <u>North</u> Line and <u>990</u> Feet From The <u>East</u> Line Section <u>30</u> Township <u>16S</u> Range <u>38E</u> NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3742' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Resume drilling, surface casing & cement <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 14-3/4" hole with rotary tools at 1:45 AM 10-24-97.

TD 480'. Reached TD at 11:15 AM 10-24-97. Ran 11 joints of 11-3/4" 42# H-40 (484.09') of casing set at 480'. 1-Texas Pattern notched guide shoe set at 480'. Insert float set at 432'. Cemented with 200 sacks BJ Lite and 2% CaCl₂ (yield 2.01, weight 12.3). Tailed in with 200 sacks Class C and 2% CaCl₂ (yield 1.32, weight 14.8). PD 6:00 PM 10-24-97. Bumped plug to 600 psi, OK. Circulated 135 sacks. WOC. Nipped up and tested to 600 psi for 15 minutes, OK. Drilled out at 9:15 AM 10-24-97. WOC 15 hours and 15 minutes. Reduced hole to 11". Resumed drilling. NOTE: Notified OCD-Hobbs prior to job.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 3, 1997
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-147

(This space for State Use)

ORIGINAL SIGNED BY CHAS WILLIAMS
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE OCT 21 1998
CONDITIONS OF APPROVAL, IF ANY:

