INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-dr or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all sp tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is t filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STAT

T Ashu	1420	rn New Mexico	Northwestern New Mexico			
In Andres_ T. lorieta T. Paddock T. Blinebry T. Tubb T. Drinkard T. Abo T. Wolfcamp T. Penn	2570 2765 3062 3710 4142 4444	T. Atoka T. Atoka T. Miss T. Devonian T. Silurian T. Montoya T. Cr. Wash T. Delaware Sand T. Bone Springs T T	T. Ojo Alamo T. Kirtland Fruitland T. Pictured Cliffs T. Cliff House T. Cliff House T. Menefee T. Point Lookout T. Mancos T. Mancos T. Gallup Base Greenhorn T. Gallup Base Greenhorn T. Dakota T. Dokota T. Morrison T. Todilto T. Entrada T. Wingate T. Chinle T. Permain	T. Penn. "B"		
No. 2, from	rate of water i	to	AS SANDS OR ZONES No. 3, from No. 4, from	to		
		LITUOLOOV DECC		* * * * * * * * * * * * * * * * * * * *		

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	То	Thickness in Feet	Lithology	Frem	lo	Thickness in Feet	Lithology
				-			
0	300	300	Surface sand, gravel &	clay			
300	1420	1120	Red Beds				
1420	1610	190	Anhydrite				
1610	2570	960	Salt				
2570	2765	195	Anhydrite & Lime				
2765	4950	2185	Dolomite & Anhydrite				
			w/Sand stringers				
							00.1
							PEId 2/13/98
					1		
				1			