Submit 3 Copies to Appropriate District Office

## State of New Mexico , Minerals and Natural Resources Departmen'

Form C-103 Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION

WELL API NO. 30-025-34198

P.O. Box 1980, Hobbs, NM 88240	
<u>DISTRICT II</u> P.O. Drawer DD, Artesia, NM 88210	

2040 Pacheco St. Santa Fe, NM 87505

Santa Fe, NM 87505	sIndicate Type of Lease
DISTRICT !! 2.O. Drawer DD, Artesia, NM 88210	STATE FEE
O. Diano. Depression	₅State Oil & Gas Lease No.
DISTRICT III 000 Rio Brazos Rd., Aztec, NM 87410	
SUNDRY NOTICES AND REPORTS ON WELLS	A Name
SUNDRY NOTICES AND REPORTS ON VELLO (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK T DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	O A  7Lease Name or Unit Agreement Name  Gandy "19"
Type of Well: GAS CTUER	Cane, 1
OIL GAS OTHER	«Well No.
2Name of Operator	1
Nearburg Producing Company	∘Pool name or Wildcat Lovington; Penn, West
3Address of Operator 3300 North "A" Street, Bldg 2, Suite 120, Midland, TX 79705	Lovington, remi, vvest
and the province	660 Feet From The East Line
4Well Location   North   Line and	600 Feet From the
Unit Letter	36E NMPM Lea County
Section 19 Township 16S Range	
**************************************	Story was a complete the story of the story
Check Appropriate Box to Indicate Nature of Notice	ce, Report, or Other Data
Check Appropriate Device	SUBSEQUENT REPORT OF:
NOTICE OF INTENTION TO:	ALTERING CASING
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	TO AND
CUANCE PLANS COMMENCE DE	RILLING OPNS.
	AND CEMENT JOB
DULL OR ALTER CASING	<u> </u>
OTHER: Surf	ace Casing and Centent
OTHER:  Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in	including estimated date of starting any proposed
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, in	···· •

work) SEE RULE 1103.

Drilled to 455'. C&C hole. RU and run 12 jts 13-3/8" 48# H40 STC casing. Set casing at 455'. Cement casing using 315 sx cement plus Diffied to 455. Cac note. No and run 12 jts 15-5/6 46# 1140 5 to casing, Set casing at 455. Certient casing using 5 to 5x certient additives. Circ 147 sx cement to surface. WOC for 12 hrs. ND BOPE, set slips, cut off casing and weld on cap. NU BOPE and test.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. TITLE Manager of Drilling and Production SIGNATURE TELEPHONE NO. 915/686-8235 TYPE OR PRINT NAME E. Scott Kimbrough ORIGINAL SIGNED BY MAR 84 197 (This space for State Use) GARY WINK DATE . FICLD REP. II APPROVED BY CONDITIONS OF APPROVAL, IF ANY: