

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-34210

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

VA-764

7. Lease Name or Unit Agreement Name

Pluma ASD State Com

8. Well No.

1

9. Pool name or Wildcat

North Feather Morrow (gas)

### SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter L : 1650 Feet From The South Line and 660 Feet From The West Line

Section 10 Township 15S Range 32E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

4296' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

#### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

#### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud, conductor, resume drilling,  
surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 10:00 AM 12-5-97. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Bonnie w/OCD-Hobbs of spud. Resumed drilling a 14-3/4" hole with rotary tools at 4:00 PM 12-10-97.

TD 432'. Reached TD at 7:45 PM 12-10-97. Ran 10 joints of 11-3/4" 42# H-40 8rd ST&C (435.71') of casing set at 432'. 1-Texas Pattern notched guide shoe set at 432'. Insert float set at 388'. Cemented with 250 sacks "C", 1/4#/sack celloflake and 2% CaCl2 (yield 1.34, weight 14.8). Tailed in with 200 sacks "C" with 2% CaCl2 (yield 1.34, weight 14.8). PD 4:00 AM 12-11-97. Bumped plug to 800 psi, OK. Circulated 25 sacks. WOC. Nipped up and tested. Drilled out at 6:45 AM 12-12-97. WOC 26 hours and 45 minutes. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Rusty Klein*

TITLE

Operations Technician

DATE

Dec. 17, 1997

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNATURE OF GREGO WILLIAMS  
DISTRICT SUPERVISOR

APPROVED BY

TITLE

DATE

DEC 23 1997

CONDITIONS OF APPROVAL, IF ANY: