

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all specific tests conducted, including drill stem tests. All depths reported shall be measured depths. In the cas of directionally drilled wells, tri-vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy 1408'
T. Salt 1592'
B. Salt 2558'
T. Yates 2748'
T. 7 Rivers 3040'
T. Queen 3695'
T. Grayburg 4130'
T. San Andr 4425'
T. Glorieta
T. Paddock
T. Blinebry
T. Tubb
T. Dinkard
T. Abo
T. Wolfcamp
T. Penn
T. Cisco (Bough C)

Northwestern New Mexico

T. Ojo Alamo
T. Kirtland Fruidland
T. Pictured Cliffs
T. Cliff House
T. Menefee
T. Point Lookout
T. Mancos
T. Gallup
Base Greehorn
T. Dakota
T. Morrison
T. Todilto
T. Entrada
T. Wingate
T. Chinle
T. Permian
T. Penn "A"

T. Penn "B"
T. Penn "C"
T. Penn "D"
T. Leadville
T. Madison
T. Elbert
T. McCracken
T. Ignacio Otzte
T. Granite
T.
T.
T.
T.
T.
T.
T.
T.

OIL OR GAS SANDS OR ZONES

No. 1, from 4695' to 4777 No. 3, from to
No. 2, from 4252' to 4475 No. 4, from to

IMPORTANT WATER SNADS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet
No. 2, from to feet
No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet in necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lighology
0	300	300	surf sand, gravel & clay				
300	1408	1108	red beds				
1408	1592	184	anhydrite				
1592	2558	966	salt				
2558	2748	190	anhydrite & lime				
2748	4900	2152	dolomite & anhydrite w/sand stringer				