-			
- Submit 3 Copies to Appropriale District Office		lew Mexico tural Resources Department	Form C-103 Revised 1-1-89
DISTRICT I P.O. Bax 1980, Habbs, NM 88240	<b>OIL CONSERV</b>	ATION DIVISION	WELL API NO.
DISTRICT II		ox 2088	30-025-34252
P.O. Drawer DD, Artesis, NM 88210	Santa Fe, New M	lexico 87504-2088	5. Indicate Type of Lesse STATE X FEE
DISTRICT III 000 Rio Brazos Rd., Aziec, NM 87410			6. State Oli & Gas Lasse No. VA-604
( DO NOT USE THIS FORM FOR F DIFFERENT RES (FORM	TICES AND REPORTS OF PROPOSALS TO DRILL OR TO D RERVOIR. USE "APPLICATION F C-101) FOR SUCH PROPOSAL	EEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
Type of Well: OL GAS WELL WELL	X) omaa	<u></u>	Field APK State Com
Name of Operator YATES PETROLEUM CORPO			8. Well No.
Address of Operator	-		9. Pool aame or Wildcat
105 South 4th St., An Well Location	tesia, NM 88210		Wildcat Morrow
	1880 Feet From The Sout	h Lipe and 165	0 Feet From The West Lin
0	140		C Feet From The Un
Section 2	Township 16S	Range 35E   whether DF, RKB, RT, GR, etc.)	NMPM Lea County
		3995' GR	
. Check	Appropriate Box to Indi	cate Nature of Notice, Re	port, or Other Data
NOTICE OF IN	Appropriate Box to Indi ITENTION TO:		port, or Other Data SEQUENT REPORT OF:
I. Check NOTICE OF IN RFORM REMEDIAL WORK	Appropriate Box to Indi ITENTION TO: PLUG AND ABANDON		
	ITENTION TO:		SEQUENT REPORT OF:
	ITENTION TO: Plug and abandon	SUB: REMEDIAL WORK	SEQUENT REPORT OF: ALTERING CASING [ OPNS. PLUG AND ABANDONMENT [
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: Plug and abandon	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEI	SEQUENT REPORT OF: ALTERING CASING [ OPNS. PLUG AND ABANDONMENT [ MENT JOB ]
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: Plug and abandon Change plans	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEI OTHER: Snubbin	SEQUENT REPORT OF: ALTERING CASING [ OPNS. PLUG AND ABANDONMENT [ MENT JOB ] 8
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: Plug and abandon Change plans	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEI OTHER: Snubbin	SEQUENT REPORT OF: ALTERING CASING [ OPNS. PLUG AND ABANDONMENT [ MENT JOB ]
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: PLUG AND ABANDON CHANGE PLANS TRAIONS (Clearly state all periment der USI lubricator. TIH Cked up 5' and set perimeted to release on, g on rams. Nippled u	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CER OTHER: Snubbing with 2.01" OD magna plug. TOOH. Rigged ft tool 3-4 times, pl0 riser pipe spool	SEQUENT REPORT OF: ALTERING CASING OPNS. PLUG AND ABANDONMENT MENT JOB g
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: PLUG AND ABANDON CHANGE PLANS TRAILORS (Clearly state all perminent der USI lubricator. TIH Cocked up 5' and set perminent der son rams. Nippled u in lines from choke Cudd N2 pump. Tested	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEN OTHER: Snubbing with 2.01" OD magna plug. TOOH. Rigged off tool 3-4 times, 10 niser pipe spon manifold to sales 1 1 BOP stack. Tried	SEQUENT REPORT OF: ALTERING CASING OPNS. PLUG AND ABANDONMENT MENT JOB g fing estimated date of starting any proposed range CIBP. Tagged 1.875" "F" down wireline. Swabbed tubing wrap around leaking. Closed ols. Rigged up space saver ine. to release packer or on/off
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: PLUG AND ABANDON CHANGE PLANS TRAIONE (Clearly state all periment data USI lubricator. TIH Loked up 5' and set periment data USI lubricator. TIH Loked up 5' and set periment data in lines from choke Cudd N2 pump. Tested case. Loaded tubing off tool. Pulled to	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEN CASING TEST AND CEN CASING TEST AND CEN OTHER: Snubbing Fails, and give persinent dates, include with 2.01" OD magna olug. TOOH. Rigged off tool 3-4 times, up 10 riser pipe spoor manifold to sales 1: i BOP stack. Tried on CIBP to elongate ubing hanger and subs	SEQUENT REPORT OF: ALTERING CASING OPNS. PLUG AND ABANDONMENT MENT JOB g g ing estimated date of starting any proposed range CIBP. Tagged 1.875" "F" down wireline. Swabbed tubing wrap around leaking. Closed ols. Rigged up space saver ine. to release packer or on/off tubing. Could not release s out. Picked up 3 joints.
NOTICE OF IN RFORM REMEDIAL WORK	TENTION TO: PLUG AND ABANDON CHANGE PLANS CHANGE PLANS TRAIONS (Clearly state all periment dat USI lubricator. TIH Cocked up 5' and set periment dat USI lubricator. TIH Cocked up 5' and set periment dat USI lubricator. TIH Cocked up 5' and set periment dat in lines from choke Cudd N2 pump. Tested case. Loaded tubing off tool. Pulled tu Worked 1 hour. Cou of packer mandrel.	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEL OTHER: Snubbin with 2.01" OD magna olug. TOOH. Rigged off tool 3-4 times, 10 riser pipe spoo manifold to sales 1: 1 BOP stack. Tried on CIBP to elongate ubing hanger and subs 1d not release. Got	SEQUENT REPORT OF: ALTERING CASING OPNS PLUG AND ABANDONMENT MENT JOB g g mg estimated date of starting any proposed range CIBP. Tagged 1.875" "F" down wireline. Swabbed tubing wrap around leaking. Closed ols. Rigged up space saver ine. to release packer or on/off tubing. Could not release s out. Picked up 3 joints. t off on/off tool. NOTE:
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: PLUG AND ABANDON CHANGE PLANS CHANGE PLANS Fallons (Clearly state all peninens def ISI lubricator. TIH Loked up 5' and set peninens def SI lubricator. TIH Loked up 5' and set peninens def in lines from choke Cudd N2 pump. Tested ase. Loaded tubing off tool. Pulled tu Worked 1 hour. Cou of packer mandrel. ding down to 11000' for se for 1-1/2 hours - 8 stands out. Rigg	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEN OTHER: Snubbin with 2.01" OD magna olug. TOOH. Rigged off tool 3-4 times, up 10 riser pipe spot manifold to sales 1 d BOP stack. Tried to on CIBP to elongate ubing hanger and subs uld not release. Got (remove fluid to allow no movement in mano- ged down snubbing uni-	SEQUENT REPORT OF: ALTERING CASING OPNS PLUG AND ABANDONMENT MENT JOB g Ing estimated date of starting any proposed range CIBP. Tagged 1.875" "F" down wireline. Swabbed tubing wrap around leaking. Closed ols. Rigged up space saver ine. to release packer or on/off tubing. Could not release s out. Picked up 3 joints. t off on/off tool. NOTE: bw more pull). Latched onto direl. Released on/off tool. it. Rigged up JSI. TIH with
NOTICE OF IN RFORM REMEDIAL WORK	TENTION TO: PLUG AND ABANDON CHANGE PLANS CHANGE PLANS Tailons (Clearly state all periment data USI lubricator. TIH cked up 5' and set periment data USI lubricator. TIH cked up 5' and set periment data in lines from choke and N2 pump. Tested ase. Loaded tubing off tool. Pulled tu Worked 1 hour. Cou of packer mandrel. ing down to 11000' for se for 1-1/2 hours - 8 stands out. Rigg e, set retrievable RE	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEL OTHER: Snubbing with 2.01" OD magna plug. TOOH. Rigged off tool 3-4 times, up 10 riser pipe spoor manifold to sales 1: d BOP stack. Tried to on CIBP to elongate ubing hanger and subs uld not release. Got (remove fluid to allo no movement in mano ged down snubbing uni BP. Set at 8000'. I ge md belief.	SEQUENT REPORT OF: ALTERING CASING OPNS PLUG AND ABANDONMENT MENT JOB g Ing estimated date of starting any proposed range CIBP. Tagged 1.875" "F" down wireline. Swabbed tubing wrap around leaking. Closed ols. Rigged up space saver ine. to release packer or on/off tubing. Could not release s out. Picked up 3 joints. t off on/off tool. NOTE: bw more pull). Latched onto drel. Released on/off tool. it. Rigged up JSI. TIH with Bled casing down. Shut well in CONTINUED ON NEXT PAGE:
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: PLUG AND ABANDON CHANGE PLANS CHANGE PLANS TRAIONS (Clearly state all periment der USI lubricator. TIH Cked up 5' and set periment der USI lubricator. TIH Cked up 5' and set periment der Son rams. Nippled u in lines from choke Cudd N2 pump. Tested ase. Loaded tubing off tool. Pulled tu Worked 1 hour. Cou of packer mandrel. Se for 1-1/2 hours - 8 stands out. Rigg e, set retrievable RH Part complete to the best of my thore lead W	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEN CASING TEST	SEQUENT REPORT OF: ALTERING CASING OPNS PLUG AND ABANDONMENT MENT JOB g
NOTICE OF IN RFORM REMEDIAL WORK	ITENTION TO: PLUG AND ABANDON CHANGE PLANS CHANGE PLANS TRAIONS (Clearly state all periment der USI lubricator. TIH Cked up 5' and set periment der USI lubricator. TIH Cked up 5' and set periment der Son rams. Nippled u in lines from choke Cudd N2 pump. Tested ase. Loaded tubing off tool. Pulled tu Worked 1 hour. Cou of packer mandrel. Se for 1-1/2 hours - 8 stands out. Rigg e, set retrievable RH Part complete to the best of my thore lead W	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEL OTHER: Snubbing with 2.01" OD magna plug. TOOH. Rigged off tool 3-4 times, up 10 riser pipe spoor manifold to sales 1: d BOP stack. Tried to on CIBP to elongate ubing hanger and subs uld not release. Got (remove fluid to allo no movement in mano ged down snubbing uni BP. Set at 8000'. I ge md belief.	SEQUENT REPORT OF: ALTERING CASING OPNS PLUG AND ABANDONMENT MENT JOB g Ing estimated date of starting any proposed range CIBP. Tagged 1.875" "F" down wireline. Swabbed tubing wrap around leaking. Closed ols. Rigged up space saver ine. to release packer or on/off tubing. Could not release s out. Picked up 3 joints. t off on/off tool. NOTE: bw more pull). Latched onto drel. Released on/off tool. it. Rigged up JSI. TIH with Bled casing down. Shut well in CONTINUED ON NEXT PAGE: chnician DATE March 26, 1999
NOTICE OF IN RFORM REMEDIAL WORK MPORARILY ABANDON LL OR ALTER CASING HER: Describe Proposed or Completed Ope work) SEE RULE 1103. 3–19–99 – Rigged up J nipple at 12220'. Pi down to 12200'. Atte BOP. Hang off tubing snubbing unit. Tied 3–20–99 – Rigged up C tool. Could not rele packer. Released on/ Latched onto packer. There is no movement 3–21–99 – Swabbed tub packer. Try to relea TOOH and snubbed last 5–1/2" shor ty wirelin reby certify that the tormatics above to the MATURE RUBET NAME	ITENTION TO: PLUG AND ABANDON CHANGE PLANS CHANGE PLANS TRAIONS (Clearly state all periment der USI lubricator. TIH Cked up 5' and set periment der USI lubricator. TIH Cked up 5' and set periment der Son rams. Nippled u in lines from choke Cudd N2 pump. Tested ase. Loaded tubing off tool. Pulled tu Worked 1 hour. Cou of packer mandrel. Se for 1-1/2 hours - 8 stands out. Rigg e, set retrievable RH Part complete to the best of my thore lead W	SUB: REMEDIAL WORK COMMENCE DRILLING CASING TEST AND CEL OTHER: Snubbing with 2.01" OD magna plug. TOOH. Rigged off tool 3-4 times, up 10 riser pipe spoor manifold to sales 1: d BOP stack. Tried to on CIBP to elongate ubing hanger and subs uld not release. Got (remove fluid to allo no movement in mano ged down snubbing uni BP. Set at 8000'. I ge md belief.	SEQUENT REPORT OF: ALTERING CASING OPNS PLUG AND ABANDONMENT MENT JOB g Ing estimated date of starting any proposed range CIBP. Tagged 1.875" "F" down wireline. Swabbed tubing wrap around leaking. Closed ols. Rigged up space saver ine. to release packer or on/off tubing. Could not release s out. Picked up 3 joints. t off on/off tool. NOTE: bw more pull). Latched onto drel. Released on/off tool. it. Rigged up JSI. TIH with Bled casing down. Shut well in CONTINUED ON NEXT PAGE: chnician DATE March 26, 1999

YATES PETROLEUM CORPORATION Field APK State Com #3 Section 2-T16S-R35E Lea County, New Mexico

## SUNDRY NOTICE CONTINUED:

3-22-99 - Loaded caisng with 170 bbls 2%. Nippled down BOP stack. Nippled down 11" 5000 X 7-1/16" 5000 tubinghead. Nippled up 11" 5000 X 7-1/16" 10K tubinghead. Nippled up BOP stack. TIH with retrieving tool, 1 joint 2-7/8" tubing, 2.312" X nipple with 2.312 pump thru plug, 1 joint 2-7/8" X nipple without plug. Rigged up snubbing unit after running 17 stands tubing. Shut down.

3-23-99 - TIH with tubing and tagged RBP. Latched on open equalizing valve. Flowed well for 2 hours. Released packer and TOOH. Closed blind rams and locked. Shut down. Flowed well overnight.

3-24-99 - Rigged up JSI lubricator. TIH with setting tool, 5-1/2" 10K wireline set Uni VI packer with 2.25" on/off profile. Below packer 2-7/8" L-80 6' sub, 2-7/8" box X 2-3/8" pinn, 1.875" "F" nipple with blanking plug in place. Set down at 7900'. Picked up, hung up and worked loose. Worked packer up hole, hanging up off and on. Hung up at 6159'. Worked 1-1/2 hours. Set packer with top at 6159'. TOOH with wireline. Bled casing down. Loaded with 114 bbls 2% KCL. Closed blinds and locked. Shut down. Monitoring 5-1/2" casing and 9-5/8" (choke line connected on 9-5/8").

3-25-99 - Picked up 4.50" OD retrieving tool, 1 joint 2-7/8", 2.312" X nipple with pump thru plug in place, 1 joint 2-7/8" tubing, 2.312" X nipple without plug. TIH with 90 stands. TIH and tagged packer at 6159'. Loaded tubing with 9.1# brine. Displaced annulus with 95 bbls at 3 BPM thru pump thru plug. Rigged up JSI. TIH and pulled pump thru plug. Landed tubing and rigged down snubbing unit. Latched into packer. Nippled down BOP stack. Nippled up 7-1/16" 5K DM tree.

3-26-99 - Nippled down manifold and flow lines. Fabricated new sales tie in. Rigged up JSI. Pressure tubing - 2500 psi + 2900 psi hydrostatic = 5400 psi at packer. TIH and pulled equalizing probe - no change in pressure. Flowed well for 2-3 minutes. TIH and latched onto plug. Released plug and TOOH. Rigged down wireline. Released well to production department.

Rustv|Kle≱∦

Operations Technician March 26, 1999