

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-34252

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

VA-604

7. Lease Name or Unit Agreement Name

Field APK State Com

8. Well No.

3

9. Pool name or Wildcat

Wildcat Morrow

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS

WELL ☒

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter K 1880 Feet From The South Line and 1650 Feet From The West Line

Section 2 Township 16S Range 35E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3995' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Production casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 12830'. Reached TD at 7:45 PM 1-19-99, Ran 308 joints of 5-1/2" 17# casing as follows: 31 joints of 5-1/2" 17# S-95 8rd sandblasted (1273.23'); 27 joints of 5-1/2" 17# S-95 8rd varnished (1136.06'); 3 joints of 5-1/2" 17# S-95 8rd sandblasted (104.82'); 3 joints of 5-1/2" 17# N-80 8rd sandblasted (126.94'); 66 joints of 5-1/2" 17# N-80 8rd varnished (2771.64'); 97 joints of 5-1/2" 17# J-55 8rd varnished (4037.31') and 81 joints of 5-1/2" 17# L-80 8rd varnished (3392.39') (Total 12842.39') of casing set at 12830'. Float shoe set at 12830'. Float collar set at 12778'. Bottom marker set at 11557'. Top marker set at 10316'. Pumped 500 gallons of Super Flush with 50 sacks of 50-50 Pozmix with 2% gel mixed at 10#/gallon ahead of 1000 sacks Super H, .4% CFR3, 5#/sack gilsonite, .4% Halad 344, 1#/sack salt and .1% HR7 (yield 1.66, weight 13.0). PD 12:15 AM 1-22-99. Bumped plug to 2590 psi for 5 minutes, OK. WOC. Released rig at 4:15 AM 1-22-99. NOTE: Notified Sylvia w/OCD-Hobbs of casing & cement. Displaced with 140 bbls fresh water and 157 sacks 2% KCL. Waiting on completion unit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Feb. 2, 1999

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNED BY DAVID WILLIAMS
DISTRICT III DIVISION

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

FEB 22 1999