

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-34252
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VA-604
7. Lease Name or Unit Agreement Name Field APK State Com
8. Well No. 3
9. Pool name or Wildcat Wildcat Morrow
10. Elevation (Show whether DF, RRB, RT, GR, etc.) 3995' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter K 1880 Feet From The South Line and 1650 Feet From The West Line
Section 2 Township 16S Range 35E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Intermediate casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4600'. Reached TD at 11:30 AM 12-15-98. Ran 104 joints of 9-5/8" 36# & 40# casing as follows: 30 joints of 9-5/8" 40# NS80 8rd ST&C (1296.02'); 72 joints of 9-5/8" 36# J-55 8rd ST&C (3226.67') and 2 joints of 9-5/8" 40# NS80 8rd ST&C (84.13') (Total 4604.40') of casing set at 4600'. Regular guide shoe set at 4593'. Float collar set at 4551'. Cemented with 950 sacks Interfill C (yield 2.71, weight 11.5). Tailed in with 250 sacks Premium Plus C with 2% CaCl2 (yield 1.34, weight 14.8). PD 1:30 AM 12-16-98. Bumped plug to 1325 psi, OK. Circulated 62 sacks. WOC. Nipple dup and tested to 5000 psi for 10 minutes, OK. Drilled out at 9:15 AM 12-17-98. WOC 31 hours and 45 minutes. Reduced hole to 8-3/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Dec. 28, 1998

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL SIGNATURE
DISTRICT OFFICE

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: