

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Departn.

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-34293
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 17921
7. Lease Name or Unit Agreement Name  State 28
8. Well No. 2
9. Pool name or Wildcat West Lovington Strawn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3993 GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator Hanley Petroleum Inc.
3. Address of Operator 415 W. Wall, Ste. 1500, Midland, Texas 79701	4. Well Location Unit Letter F : 2310 Feet From The North Line and 1650 Feet From The West Line Section 32 28 Township 15S Range 35E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5/13/98 TD @ 12,000'. Ran CNL, LDT, DIFL, GR logs.

5/14/98 Ran 88 jts 4 1/2" 11.60# N-80, 89 jts 4 1/2" 11.60# J-55, 94 jts 4 1/2" 11.60# N-80 casing. Casing set @ 12,000'. Halliburton cemented w/400 sx Interfill H & 800 sx 50-50 POZ w/2% gel.

5/15/98 Ran temperature survey and found TOC @ 6888'.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Greg Wilkes TITLE VP Engineering DATE 5/18/98  
TYPE OR PRINT NAME Greg Wilkes TELEPHONE NO. 915-684-8051

(This space for State Use)

APPROVED BY CHRIS WILLIAMS TITLE SUPERVISOR DATE 5/18/98

CONDITIONS OF APPROVAL, IF ANY: