

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO	30-025-34354
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	B-10629
7. Lease Name or Unit Agreement Name	
Big Flat ASN State Com	
8. Well No.	1
9. Pool name or Wildcat	Townsend Morrow

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210	4. Well Location Unit Letter J : 1650 Feet From The South Line and 1980 Feet From The East Line Section 10 Township 16S Range 35E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3997' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Resume drilling, surface casing & cmt ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Resumed drilling a 17-1/2" hole with rotary tools at 12:00 PM 4-15-98.

TD 460'. Reached TD at 8:00 PM 4-15-98. Ran 10 joints of 13-3/8" 54.5# J-55 (463.01') of casing set at 460'. 1-Texas Pattern notched guide shoe set at 460'. Insert float set at 414'. Cemented with 475 sacks Class C and 2% CaCl₂ (yield 1.34, weight 14.8). PD 3:45 AM 4-16-98. Bumped plug to 700 psi, OK. Circulated 195 sacks. WOC. Nipped up and tested to 500 psi for 15 minutes, OK. Drilled out at 4:00 PM 4-17-98. WOC 36 hours and 15 minutes. Reduced hole to 12-1/4". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 27, 1998

TYPE OR PRINT NAME Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

ORIGINAL FILED BY CHRIS WILLIAMS
ESTATE SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: