

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-34399

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Quarry

8. Well No.

1

9. Pool name or Wildcat

Wildcat Strawn

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OR
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Manzano Oil Corporation 505/623-1996

3. Address of Operator

P.O. Box 2107/Roswell, NM 88202-2107

4. Well Location

Unit Letter 0/15 : 3526 Feet From The South Line and 2095 Feet From The East Line

Section 3

Township 16 South

Range 36 East

NMMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3911' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2/05/99 Set 50 sks Class H w/0.2% R3 from 11,657' back to 11,557'.
Set 115 sks Class H from 10,877' back to 10,677'.
Set 35 sks Class C Neat plug from 8004' back to 7904'.
Set 35 sks Class C Neat plug from 6525' back to 6425'.
Set 35 sks Class C + 2% CaCl plug from 4418' back to 4318' - 50' in and
out of 8-5/8" csg shoe.
Set 30 sks Class C Neat plug from 2103' back to 2003'.
Set 30 sks Class C + 2% CaCl plug from 470' back to 370' - 50' in and out
of 13-3/8" surface csg.
Set 10 sks surface plug.
Well P&A.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

D.E. Brown

TITLE

VP Engineering

DATE

2/16/99

TYPE OR PRINT NAME

D.E. Brown

TELEPHONE NO. 623-1996

(This space for State Use)

APPROVED BY

Billy E. Prebun

TITLE

OIL & GAS INSPECTOR

DATE

CONDITIONS OF APPROVAL, IF ANY:

TC HWW

dp