

Carlisle 1-y  
1721' FSL & 1909' FWL  
Sec. 10, T-16-S, R-35-E  
Lea Co., NM

Elevation: 3998' GL, 4015' KB

## Proposed Atoka Completion

Spud Date:  
Completion Date: July 1998

### Completion

13-3/8" Surface casing?

9-5/8" Intermediate set at  
4750'

Pkr Fluid: 2% KCl water w/  
corrosion inhibitor and O<sub>2</sub>  
scavenger

2-7/8" tbg

Baker L-10 On/off tool w/2.313" "F" profile

Arrowset I pkr @ 11,600'  
WL entry guide @ 11,615'

Upper Atoka Perfs:  
11,572-74' & 11,577-93'

Fat Lady Atoka Perfs:  
11,710-14' & 11,725-27'

CIBP @ 12,000' w/20' cmt

Carlisle Perfs:  
(4 spf)  
12068' - 120'

Spacer -2 jts 2-3/8" L80 tbg  
Mechanical firing head  
11' safety spacer  
TCP gun assy. loaded 4 spf 60  
deg.  
Top of TCP assy +/- 12,191'

5-1/2" 17# N-80 & S-95 @ 12,370'  
TOC Unknown

TD: 12,375'  
PBD: 12,323'  
(approx.)