

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-34443
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	Runnels ASP
8. Well No.	2
9. Pool name or Wildcat	Shoe Bar Strawn, North

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter J : 1650 Feet From The South Line and 2270 Feet From The East Line

Section 11 Township 16S Range 35E NMMPM Lea County
10. Elevation (Show whether DF, RRB, RT, GR, etc)
3997' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER: ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Perforate & acidize Strawn ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-7-99 - Moved in and rigged up pulling unit. Rigged up slickline. TIH with FSG 10000# 1.81" blanking plug. Set plug in 1.81" F nipple at 11968'. TOOH with slickline. Rigged down slickline. Bled tubing down. Loaded tubing with 2% KCL with surfactants. Tested blanking plug to 1000 psi. Nippled down tree and nipped up BOP. Get off Arrowset packer. TOOH with tubing and on/off tool. Rigged up wireline. TIH with wireline set RBP and set RBP at 11580'. Tested RBP to 1500 psi, OK. Dumped 1 sack of 20-40 sand on RBP. Rigged down wireline.

4-8-99 - Rigged up wireline and lubricator. TIH with 4" casing guns and perforated 11508-11524' w/68 .42" holes (4 SPF - Strawn Sand). TOOH with casing guns and rigged down wireline. TIH with packer with 1.875" on/off tool and tubing. Set packer at 11412'. Nippled down BOP and nipped up tree. Tested packer and tree to 1000 psi, OK. Swabbed. Shut well in overnight.

4-9-99 - Acidized perforations 11508-11524' with 500 gallons of 7-1/2% iron control HCL acid. Swabbed. Shut well in overnight.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CONTINUED ON NEXT PAGE:

SIGNATURE Rusty Klein TITLE Operations Technician DATE April 12, 1999

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: