YATES PETROLEUM CORPORATION Runnels ASP #2 Section 11-T16S-R35E Lea County, New Mexico

SUNDRY NOTICE CONTINUED:

down tree and nippled up BOP. Released packer. Reversed 120 bbls. TOOH with tubing and packer. TIH with knock out plug and tailpipe, packer and tubing. Set packer at 11609'. Tested to 1000 psi, OK. Dropped bar. Knocked out plug. Well started gassing. Tested packer to 1000 psi, OK. Swabbed.
10-3-98 - Rigged up treesaver. Attempted to frac - shut down. Rigged down treesaver. Bled well down. Pumped 70 bbls 2% KCL down tubing. Nippled down tree. Nippled up BOP. Released packer. TOOH with tubing and packer. Rigged up Bo Monk pipe testers. TIH with 1.81" F nipple, 10 joints tailpipe, Arrow-set packer and tubing. Tested tubing to 10000 psi, OK. Nippled down BOP and nippled up tree. Set packer at 11641'. Tested packer and tree to 2500 psi, OK. Swabbed well down.
10-4-98 - Rigged up treesaver. Frac'd perforations 12008-12025' (Atoka) with 39500

gallons 70Q binary foam, 3000 gallons methanol 40# CMHPG, 70 tons CO2, 450000 scf N2 and 47000# 20-40 Interprop. Rigged down treesaver. Shut well in for 2 hours. Opened well up and flowing back frac. Shut well in.

10-5-98 - Flowed back. Shut well in.

10-6-98 - Released well to production department.

Rusty Kle/ln

Operations Technician October 8, 1998