

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO.
30-025-34466

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

7. Lease Name or Unit Agreement Name

Cartwright 7

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER Dry Hole

8. Well No.
1

2. Name of Operator
Chesapeake Operating, Inc.

9. Pool name or Wildcat
NE Lovington Penn

3. Address of Operator
P.O. Box 18496, Oklahoma City, OK 73154-0496

4. Well Location
Unit Letter E : 2088 Feet From The North Line and 812 Feet From The West Line
Section 7 Township 16S Range 37E NMPM LEA County

10. Elevation (Show whether DP, RKB, RT, GR, etc.)
GR: 3852'

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐
OTHER: Rig Release ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

04/22/00 TIH w/DC's, cut drlg line, single down DP, TIH w/DP open ended to plug well. Circ, pump 35 sx plug 11,779-679', single down DP, pump 35 sx plug 9,782-9,682', single down DP, pump 35 sx plug 7769'-7664', single down DP, pump 35 sx plug 6533-6433', single down DP, pump 35 sx plug 4500-4400', pull 3 stds, circ, WOC 24 hrs, TIH, tag cmt plug @9391', break kelly, single down DP.

04/23/00 Single down DP, pump plug @2150-2050', single down DP, plump plug @500'-400', single down DP, WOC, tag cmt, plug w/ WL 3405', pull wear ring, pump 10 sx surface plug, LD 8 jts, ND BOPs, cut off 8-5/8" csg 4' below ground level, weld on plate & dry hole marker, jet & clean pits.

Release Patterson Drilling rig #48 @2:00 p.m. on 4/23/00

Approved as to plugging of the Well Bore.
Liability under bond is retained until
surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Barbara J. Bale TITLE Regulatory Analyst DATE 05/02/00

TYPE OR PRINT NAME Barbara J. Bale TELEPHONE NO. (405) 848-8000

(This space for State Use)

APPROVED BY GARY W. WINK TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE JAN 28 2003

CONDITIONS OF APPROVAL, IF ANY

G W W