

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-34498
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	V-4415

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☒ OTHER

2. Name of Operator
YATES PETROLEUM CORPORATION

3. Address of Operator
105 South 4th St., Artesia, NM 88210

4. Well Location
Unit Letter H : 1650 Feet From The North Line and 700 Feet From The East Line

Section 15 Township 16S Range 32E NMMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4304' GR

7. Lease Name or Unit Agreement Name

Ruby ASV State Com

8. Well No.
1

9. Pool name or Wildcat
Anderson Ranch Morrow (gas)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud, conductor, surface casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 20" hole with rat hole machine at 2:20 PM 10-25-98. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Gary Wink w/OCD-Hobbs of spud. Resumed drilling a 14-3/4" hole with rotary tools at 8:00 AM 10-28-98..

TD 400'. Reached TD at 12:30 PM 10-28-98. Ran 9 joints of 11-3/4" 42# H-40 8rd ST&C (405.52') of casing set at 400'. 1-Texas Pattern notched guide shoe set at 400'. Insert float set at 354'. Cemented with 400 sacks "C" with 2% CaCl2 (yield 1.34, weight 13.9). PD 5:45 PM 10-28-98. Bumped plug to 450 psi, OK. Circulated 55 sacks. WOC. Cut off and welded on head for rotating head. Drilled out at 11:45 AM 10-29-98. WOC 18 hours. Reduced hole to 11". Resumed drilling. NOTE: Notified Sylvia w/OCD-Hobbs of cementing - no witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE Nov. 5, 1998

TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: