

Prince Nymph #1

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt 2100'	T. Strawn 11,764'
B. Salt	T. Atoka
T. Yates 3151'	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres 4785'	T. Simpson
T. Glorieta 6337'	T. McKee
T. Paddock	T. Ellenburger
T. Blinebry 6972'	T. Gr. Wash
T. Tubb 7605'	T. Delaware Sand
T. Drinkard 7822'	T. Bone Springs
T. Abo 8390'	T.
T. Wolfcamp 9840'	T. Tansil
T. Penn	T. 3 Bros.
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. _____
T. Morrison _____	T. _____
T. Todilto _____	T. _____
T. Entrada _____	T. _____
T. Wingate _____	T. _____
T. Chinle _____	T. _____
T. Permian _____	T. _____
T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
3900'	4820'	920'	Dolomite & Anhydrite w/minor Shale
4820'	5800'	980'	Dolomite
5800'	5920'	120'	Limestone
5920'	9020'	3100'	Dolomite
9020'	9840'	820'	Dolomite & Limestone
9840'	11,120'	1280'	Limestone w/minor Shale
11,120'	11,660'	540'	Shale w/minor Limestone
11,660'	12,000'	340'	Limestone
12,000'	12,052'	52'	Sandstone
			TD

From	To	Thickness In Feet	Lithology