

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

811 South First, Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO.  
30-025-34607

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
24466

7. Lease Name or Unit Agreement Name:

Royal Humpy

8. Well No.

1

9. Pool name or Wildcat  
Diamond Strawn

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
David H. Arrington Oil & Gas, Inc

3. Address of Operator  
P.O. Box 2071, Midland, Texas 79702

4. Well Location

Unit Letter I : 1615' feet from the South line and 1161' feet from the East line

Section 16 Township 16S Range 36E NMPM County Lea

10. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3904' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Repair Rod Valve ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/18/01 - MIRU Key Well Service. POOH with rods & pump. Found valve rod broken, BBL grooved & scored. GIH w/rods & pump as follows: 1 - 1 1/2" x 26' polish rod with 1 3/4" x 1 1/2" x 16' liner, 1 - 1" x 8' sub, 2 - 1" x 6' subs, 1 - 1" x 2' sub, 121 - 1" "D" rods, 126 - 7/8" "D" rods, 165 - 3/4" "D" rods, 38 - 1" "D" rods, 10 - 1 3/4" sinker bars, 2' x 1" x 7/8" rod guide, 2" x 1 1/2" x 20' x 6' x 4' pump with 1" x 14' gas anchor. Load 2 7/8" tubing with 53 bbls produced water and pressure to 500 psi- OK. Left well pumping 5 SPM x 125" LS. Rig down Key Well Service.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Chuck Sledge TITLE Engineer

DATE 11/07/01

Type or print name Chuck Sledge

Telephone No. (915) 682-6685

(This space for State use)

APPROVED BY

TITLE

PAUL E. KAUFZ  
PETROLEUM ENGINEER

DATE 11/5/2001

Conditions of approval, if any:

