

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-34631
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Shell Lusk ANB
8. Well No. 2
9. Pool name or Wildcat Big Dog Strawn, South

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. Name of Operator YATES PETROLEUM CORPORATION	
3. Address of Operator 105 South 4th St., Artesia, NM 88210	
4. Well Location Unit Letter <u>E</u> : <u>1950</u> Feet From The <u>North</u> Line and <u>350</u> Feet From The <u>West</u> Line Section <u>11</u> Township <u>16S</u> Range <u>35E</u> NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3990' GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Intermediate casing & cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 4725'. Reached TD at 10:00 PM 6-20-99. Ran 109 joints of 9-5/8" 40# & 36# casing as follows: 59 joints of 9-5/8" 40# NS80 8rd ST&C (2627.93'); 45 joints of 9-5/8" 36# J-55 8rd ST&C (2016.46') and 2 joints of 9-5/8" 40# NS80 8rd ST&C (90.10') (Total 4734.49') of casing set at 4725'. Float shoe set at 4725'. Float collar set at 4665'. Cemented with 1200 sacks Interfill C and 1/4#/sack flocele (yield 2.46, weight 11.9). Tailed in with 250 sacks Premium Plus and 2% CaCl2 (yield 1.34, weight 14.8). PD 3:00 PM 6-21-99. Bumped plug to 1755 psi, OK. Circulated 148 sacks. WOC. Nipped up and tested to 5000 psi for 30 minutes. Drilled out at 12:30 PM 6-23-99. WOC 45 hours and 30 minutes. Reduced hole to 8-3/4". Resumed drilling. NOTE: Notified Sylvia w/OCD-Hobbs of cementing - no witness.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rusty Klein TITLE Operations Technician DATE July 9, 1999
TYPE OR PRINT NAME Rusty Klein TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: