

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-025-34645
Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No. 004684
Lease Name or Unit Agreement Name Snyder "F"
Well No. 3
Pool name or Wildcat Lovington Strawn, West

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
Name of Operator Charles B. Gillespie, Jr.
Address of Operator P.O. Box 8, Midland, Texas 79702
Well Location Unit Letter D 330 Feet From The West Line and 655 Feet From The North Line 5 Section 16S Township 36E Range NMPM Lea County
Elevation (Show whether DF, RKB, RT, GR, etc.)

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

09/02/99 Finished drilling 11" hole to 4750'. POOH. RIH w/117 jts 8-5/8" 32# J-55 & Mav-80 csg. Landed casing shoe @ 4750'. RU cementers & cemented 8-5/8" csg w/950 sx class "C" 10% bentonite followed by 200 sx class "C" w/1%CaCl2. Plug down @ 2:50 AM, 09/03/99. Set slips. Cut off csg.

09/03/99. Weld on head. NU BOPs. Yellow jacketed BOPs & choke manifold to 5000 psi. PU & RIH w/7-7/8" bit, tag cmt @ 4623'. Press test pipe rams & csg to 1500 psi. Drill out cmt & float. Drill out shoe 22 1/2 hrs after plug down.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mark Mladenka TITLE Production Manager DATE 09-08-99

TYPE OR PRINT NAME Mark Mladenka

TELEPHONE NO. (915)683-1765

(This space for State Use)

ORIGINAL SIGNATURE OF WILLIAM
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY

SEP 27 1999

