Submit 3 Copies to Appropriate District Office

State of New Mexico E. gy, Minerals and Natural Resources Departmen.

Form C-100

CONDITIONS OF APPROVAL, IF ANY:

Revised 1-1-89

DISTRICT I P.O. Box 1980, Hobba, NM 88240	OIL CONSERVATION DIVISION P.O. Box 2088		WELL API NO.
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 87504-2088		30-025-34688 5. Indicate Type of Lease	
DISTRICT III 1000 Rio Brazos Rd., Aziec, NM 87410			STATE X FEE 6. State Oil & Gas Lesse No. VA-478
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			7. Lease Name or Unit Agreement Name
1. Type of Well: Oil GAS WELL WELL X	OTHER		Gallagher ATJ State Com
2. Name of Operator YATES PETROLEUM CORPOR.	ATION		8. Well No.
3. Address of Operator			9. Pool name or Wildcat
105 South 4th St., Arte	esia, NM 88210		Eidson Mississippian
Unit Letter G: 2300 Feet From The North Line and 2300 Feet From The East Line			
Section 2 Township 16S Range 35E NMPM Lea County			
10. Elevation (Show whether DF, RKB, RT, GR, etc.)			
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data			
NOTICE OF INT			SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT			
PULL OR ALTER CASING CASING TEST AND CEMENT JOB			
OTHER: OTHER: Intermedia		iate casing & cement X	
12. Describe Proposed or Completed Operations (Clearly state all periment details, and give periment dates, including estimated date of starting any proposed work) SEER RULE 1103. TD 4642'. Reached TD at 10:00 AM 10-7-99, Ran 112 joints of 8-5/8" 32# Mav 80 and J-55 (4646.30') of casing set at 4642'. Regular guide shoe set at 4642'. Float collar set at 4600'. Cemented with 1400 sacks Class C Poz (65-35-6), 5#/sack salt, 1/4#/sack celloflake (yield 2.03, weight 12.5). Tailed in with 200 sacks Class C and 2% CaCl2 (yield 1.34, weight 14.8). PD 11:45 PM 10-7-99. Bumped plug to 2050 psi, OK. Circulated 138 sacks. WOC. Nippled up and tested to 1000 psi for 15 minutes, OK. Drilled out at 6:00 AM 10-9-99. WOC 30 hours nad 15 minutes. Reduced hole to 7-7/8". Resumed drilling. NOTE: Notified Sylvia w/OCD-Hobbs of casing and cement job - did not witness.			
I hereby certify that the information above to true	and complete to the best of my knowledge and		
SIGNATURE Pusting The	<u>√</u> π	Operations Te	chnician Oct. 12, 1999
TYPEOR PRINT NAME Rusty Klein			TELEPHONE NO. 505/748-14
(This space for State Use) ORIGINAL SIG			OCT 1 8 1999
APPROVED BY	m	LB	DATS