Submit 3 Copies to Appropriate District Office	State of New Energy, Minerals and Natural		Form C-103 Revised 1-1-89
DISTRICT I P.O. Box 1980, Hobbs, NM 88240 DISTRICT II	OIL CONSERVAT P.O. Box Santa Fe, New Mexic	2088	WELL API NO. 30-025-34688
P.O. Drawer DD, Artesia, NM 88210 DISTRICT III			5. Indicate Type of Lease STATE STATE FEE
1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Gas Lease No. VA-478
(DO NOT USE THIS FORM FOR PI DIFFERENT RES	TICES AND REPORTS ON V ROPOSALS TO DRILL OR TO DEEF ERVOIR. USE "APPLICATION FOR C-101) FOR SUCH PROPOSALS.)	PEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
1. Type of Well: OIL OAS WELL WELL			Gallagher ATJ State Com
2. Name of Operator YATES PETROLEUM CORPO			8. Well No.
3. Address of Operator	RAIION		9. Pool name or Wildcat
105 South 4th St., Ar 4. Well Location	tesia, NM 88210		Eidson Mississippian
	300 Feet From The North	1 Line and 230	00 Feet From The East Li
ŋ	1/2		
Section 2	Township 16S	Range 35E ther DF, RKB, RT, GR, etc.)	NMPM Lea County
		3991' GR	
	Appropriate Box to Indica		eport, or Other Data
	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
	CHANGE PLANS	COMMENCE DRILLIN CASING TEST AND C	
PULL OR ALTER CASING		CASING TEST AND C	GOPNS. PLUG AND ABANDONMENT EMENT JOB
PULL OR ALTER CASING	[CASING TEST AND C OTHER: Spud, co	GOPNS. PLUG AND ABANDONMENT EMENT JOB onductor, resume drilling, casing & cement
PULL OR ALTER CASING	erations (Clearly state all pertinent detail	CASING TEST AND C OTHER: Spud, co surface b, and give periment dates, inclu- at 1:00 PM 9-26-9 ied OCD-Hobbs of	GOPNS. PLUG AND ABANDONMENT EMENT JOB
PULL OR ALTER CASING	erations (Clearly state all persistent detail ith rat hole machine a urface. NOTE: Notif: tary tools at 10:45 AN at 8:00 PM 9-28-99. '. 1-Texas Pattern no ed with 150 sacks Class 5, weight 12.5). Tai 14.8). PD 1:05 PM 9- 00. Cut off and weld	CASING TEST AND C OTHER: Spud, co surface b, and give periment dates, inclu- at 1:00 PM 9-26-9 ied OCD-Hobbs of M 9-27-99. Ran 10 joints of otched guide shoe ss C Poz (65-35), led in with 200 s 28-99. Bumped pl ed on flow nipple	BOPNS. PLUG AND ABANDONMENT EMENT JOB Denductor, resume drilling, casing & cement ding estimated date of starting any proposed 9. Set 40' of 16" conductor spud. Resumed drilling a 11-3/4" 42# H-40 (429.08') set at 425'. Insert float 5#/sack gilsonite and 6% acks Class C with 2% CaCl2 ug to 640 psi, 0K. Circulated . Drilled out at 9:00 AM
PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed Opwork) SEE RULE 1103. Spudded a 20" hole w pipe. Cemented to sr 14-3/4" hole with ro TD 425'. Reached TD of casing set at 425 set at 382'. Cement bentonite (yield 1.9 (yield 1.34, weight 130 sacks cement. W 9-29-99. WOC 19 hou Ihereby certify that the information above is	erations (Clearly state all pertinent detail ith rat hole machine a urface. NOTE: Notif: tary tools at 10:45 AM at 8:00 PM 9-28-99. '. 1-Texas Pattern no ed with 150 sacks Class 5, weight 12.5). Tail 14.8). PD 1:05 PM 9- 0C. Cut off and weld rs and 55 minutes. Re	CASING TEST AND C OTHER: Spud, co surface b, and give periment dates, inclu- at 1:00 PM 9-26-94 ied OCD-Hobbs of M 9-27-99. Ran 10 joints of otched guide shoe ss C Poz (65-35), led in with 200 s 28-99. Bumped pl ed on flow nipple educed hole to 11	GOPNS. PLUG AND ABANDONMENT EMENT JOB onductor, resume drilling, casing & cement ding estimated date of starting any proposed 9. Set 40' of 16" conductor spud. Resumed drilling a 11-3/4" 42# H-40 (429.08') set at 425'. Insert float 5#/sack gilsonite and 6% acks Class C with 2% CaCl2 ug to 640 psi, OK. Circulated . Drilled out at 9:00 AM ". Resumed drilling.
PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed Opwork) SEE RULE 1103. Spudded a 20" hole w pipe. Cemented to sr 14-3/4" hole with ro TD 425'. Reached TD of casing set at 425 set at 382'. Cement bentonite (yield 1.9 (yield 1.34, weight 130 sacks cement. W 9-29-99. WOC 19 hou Ihereby certify that the information above in SKONATURE	erations (Clearly state all pertinent detail ith rat hole machine a urface. NOTE: Notif: tary tools at 10:45 AM at 8:00 PM 9-28-99. '. 1-Texas Pattern no ed with 150 sacks Class 5, weight 12.5). Tail 14.8). PD 1:05 PM 9-2 0C. Cut off and weld rs and 55 minutes. Re prue and compide to the best of my knowledge	CASING TEST AND C OTHER: Spud, co surface b, and give periment dates, inclu- at 1:00 PM 9-26-94 ied OCD-Hobbs of M 9-27-99. Ran 10 joints of otched guide shoe ss C Poz (65-35), led in with 200 s 28-99. Bumped pl ed on flow nipple educed hole to 11	GOPNS. PLUG AND ABANDONMENT EMENT JOB Donductor, resume drilling, casing & cement ding estimated date of starting any proposed 9. Set 40' of 16" conductor spud. Resumed drilling a 11-3/4" 42# H-40 (429.08') set at 425'. Insert float 5#/sack gilsonite and 6% acks Class C with 2% CaCl2 ug to 640 psi, OK. Circulated . Drilled out at 9:00 AM ". Resumed drilling.
PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed Opwork) SEE RULE 1103. Spudded a 20" hole w pipe. Cemented to si 14-3/4" hole with ro TD 425'. Reached TD of casing set at 425 set at 382'. Cement bentonite (yield 1.9 (yield 1.34, weight 130 sacks cement. W 9-29-99. WOC 19 hou I hereby certify that the information shore is skinkature TYPE OR PRINT NAME Rusty K1e Type OR PRINT NAME	The and complete to the best of my knowledge true and complete to the best of my knowledge true and complete to the best of my knowledge in	CASING TEST AND C OTHER: Spud, co surface b, and give periment dates, inclu- at 1:00 PM 9-26-94 ied OCD-Hobbs of M 9-27-99. Ran 10 joints of otched guide shoe ss C Poz (65-35), led in with 200 s 28-99. Bumped pl ed on flow nipple educed hole to 11	GOPNS. PLUG AND ABANDONMENT EMENT JOB Denductor, resume drilling, casing & cement ding estimated date of starning any proposed 9. Set 40' of 16" conductor spud. Resumed drilling a 11-3/4" 42# H-40 (429.08') set at 425'. Insert float 5#/sack gilsonite and 6% acks Class C with 2% CaCl2 ug to 640 psi, OK. Circulated . Drilled out at 9:00 AM ". Resumed drilling. TELEPHONE NO. 505/748
PULL OR ALTER CASING DTHER: 12. Describe Proposed or Completed Opwork) SEE RULE 1103. Spudded a 20" hole w pipe. Cemented to si 14-3/4" hole with ro TD 425'. Reached TD of casing set at 425 set at 382'. Cement bentonite (yield 1.9 (yield 1.34, weight 130 sacks cement. W 9-29-99. WOC 19 hou I hereby certify that the information shore is skinkature TYPE OR PRINT NAME Rusty K1e Type OR PRINT NAME	The and complete to the best of my knowledge in the set o	CASING TEST AND C OTHER: Spud, co surface b, and give periment dates, inclu- at 1:00 PM 9-26-94 ied OCD-Hobbs of M 9-27-99. Ran 10 joints of otched guide shoe ss C Poz (65-35), led in with 200 s 28-99. Bumped pl ed on flow nipple educed hole to 11	GOPNS. PLUG AND ABANDONMENT EMENT JOB Donductor, resume drilling, casing & cement ding estimated date of starting any proposed 9. Set 40' of 16" conductor spud. Resumed drilling a 11-3/4" 42# H-40 (429.08') set at 425'. Insert float 5#/sack gilsonite and 6% acks Class C with 2% CaCl2 ug to 640 psi, OK. Circulated . Drilled out at 9:00 AM ". Resumed drilling.