

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	True Vertical Depth	N-S FT	E-W FT	Vertical Section FT	C L O S U R E		Dogleg Severity Deg/100
				FT	FT	FT	Distance FT	Direction Deg	
10744.00	.70	269.50	10743.16	-51.71	-41.35	-42.05	66.21	218.65	.02
10915.00	.90	257.60	10914.14	-52.00	-43.70	-44.41	67.93	220.04	.15
Side Track Point									
10930.00	.94	261.21	10929.14	-52.05	-43.94	-44.65	68.12	220.17	.49
10979.00	1.30	60.10	10978.13	-51.83	-43.86	-44.57	67.90	220.24	4.51
11010.00	5.00	76.20	11009.08	-51.33	-42.24	-42.94	66.48	219.45	12.16
11040.00	9.10	78.60	11038.85	-50.55	-38.64	-39.34	63.63	217.40	13.70
11072.00	12.90	82.40	11070.26	-49.58	-32.62	-33.30	59.35	213.34	12.08
11103.00	17.00	86.10	11100.20	-48.81	-24.67	-25.33	54.69	206.81	13.57
11135.00	21.00	87.80	11130.45	-48.28	-14.27	-14.93	50.34	196.46	12.62
11166.00	26.20	88.60	11158.85	-47.90	-1.86	-2.52	47.93	182.23	16.81
11198.00	32.30	88.40	11186.76	-47.48	13.76	13.10	49.44	163.84	19.06
11230.00	37.90	88.90	11212.93	-47.06	32.15	31.50	56.99	145.66	17.52
11261.00	43.70	88.60	11236.38	-46.61	52.39	51.74	70.12	131.66	18.72
11293.00	49.80	88.50	11258.30	-46.02	75.68	75.04	88.57	121.30	19.06
11324.00	55.10	88.00	11277.18	-45.27	100.23	99.60	109.98	114.30	17.14
11355.00	60.60	87.70	11293.67	-44.28	126.45	125.83	133.98	109.30	17.76
11372.00	63.60	87.40	11301.63	-43.64	141.46	140.85	148.04	107.14	17.72
11407.00	63.70	87.40	11317.16	-42.21	172.79	172.20	177.87	103.73	.29
Top of Strawn									
11434.00	65.93	87.40	11328.65	-41.11	197.20	196.62	201.44	101.77	8.28
11436.00	66.10	87.40	11329.46	-41.02	199.02	198.44	203.21	101.65	8.28
Top of Porosity									
11446.00	67.40	88.90	11333.41	-40.73	208.21	207.63	212.15	101.07	18.95
11456.00	68.00	88.30	11337.21	-40.50	217.46	216.88	221.20	100.55	8.17
11468.00	68.70	87.90	11341.63	-40.13	228.60	228.03	232.10	99.96	6.61
11500.00	71.50	87.20	11352.52	-38.84	258.66	258.10	261.56	98.54	8.99
11510.00	72.80	87.10	11355.59	-38.37	268.17	267.62	270.90	98.14	13.03
11531.00	74.00	87.40	11361.59	-37.40	288.27	287.73	290.69	97.39	5.88
11563.00	76.00	87.50	11369.87	-36.03	319.15	318.62	321.17	96.44	6.26
11578.00	76.10	87.50	11373.49	-35.39	333.69	333.17	335.56	96.05	.67
11595.00	76.30	87.20	11377.54	-34.63	350.18	349.67	351.89	95.65	2.08
Interpolated Point									
11600.00	76.38	87.15	11378.72	-34.39	355.04	354.53	356.70	95.53	1.81
11627.00	76.80	86.90	11384.98	-33.03	381.26	380.77	382.69	94.95	1.81
11658.00	77.00	86.90	11392.01	-31.40	411.41	410.94	412.61	94.36	.65
11668.00	77.30	87.20	11394.24	-30.90	421.15	420.69	422.28	94.20	4.19
11689.00	78.70	88.10	11398.60	-30.05	441.67	441.22	442.69	93.89	7.88
11699.00	79.60	88.50	11400.48	-29.76	451.49	451.04	452.47	93.77	9.82
11709.00	80.50	88.40	11402.21	-29.50	461.34	460.89	462.28	93.66	9.05
11721.00	81.00	88.30	11404.14	-29.15	473.17	472.73	474.07	93.53	4.25
11731.00	81.90	88.20	11405.63	-28.85	483.06	482.62	483.92	93.42	9.05